

Remonumentation of Certain Original Corner Points,  
T. 6 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 10 W  
S 11 | S 12  
S 14 | S 13  
1979

from which new bearing trees

A hemlock, 11 ins. diam., bears S. 36° E., 19½ lks. dist., mkd. T6S R10W S13 BT.

A hemlock, 9 ins. diam., bears S. 51½° W., 54 lks. dist., mkd. T6S R10W S14 BT.

The ¼ sec. cor. of secs. 11 and 12, determined at record distance from the remains of the original bearing trees:

A sawed hemlock stump, 24 ins. diam., bears S. 26° E., 11 lks. dist., with healed blaze. (Record, spruce, S. 13° E.)

A sawed hemlock stump, 24 ins. diam., bears N. 32½° W., 13 lks. dist., with scribe marks ¼ S visible on opened blaze. (Record, N. 52° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 10 W  
¼  
S 11 | S 12  
1979

from which new bearing trees

A hemlock, 6 ins. diam., bears S. 65½° E., 6½ lks. dist., mkd. ¼ S12 BT.

A hemlock, 6 ins. diam., bears S. 30° W., 7 lks. dist., mkd. ¼ S11 BT.

The ¼ sec. cor. of secs. 1 and 2, monumented with an iron pipe, 1 in. diam., firmly set, projecting 20 ins. above ground, from which the remains of the original bearing trees:

A sawed hemlock stump, 22 ins. diam., bears S. 6° E., 39 lks. dist., with scribe marks BT visible on opened blaze. (Record, S. 10° E.)

A sawed hemlock stump, 22 ins. diam., bears N. 39° W., 4 lks. dist., with fragmentary scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.