

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 10 W., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{2}$ sec. cor. of secs. 13 and 14, monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 36 ins. above ground, from which the remains of the original bearing trees:

A root hole, bears N. $31\frac{1}{2}^{\circ}$ E., 24 lks. dist., with a down hemlock alongside, 24 ins. diam., with healed blaze.

A sawed hemlock stump, 37 ins. diam., bears S. 88° W., 22 lks. dist., with scribe marks $\frac{1}{4}$ S visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 10 W

$\frac{1}{4}$
S 14 | S 13
1979

from which new bearing trees

A hemlock, 5 ins. diam., bears N. 48° E., 17 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

A hemlock, 5 ins. diam., bears N. $63\frac{1}{2}^{\circ}$ W., 6 lks. dist., mkd. $\frac{1}{4}$ S14 BT.

Reset iron pipe alongside iron post.

The cor. of secs. 11, 12, 13, and 14, determined at record bearing and distance from the remains of the original bearing trees:

A decayed hemlock stump, 16 ins. diam., bears N. 31° E., 11 lks. dist., with scribe marks BT visible on opened blaze.

A decayed hemlock stump, 6 ins. diam., bears S. 87° E., 11 lks. dist., no marks visible.

A spruce snag, 36 ins. diam., bears S. 22° W., 6 lks. dist., with healed blaze.

A decayed hemlock stump, 9 ins. diam., bears N. $61\frac{1}{2}^{\circ}$ W., 7 lks. dist., with scribe marks BT visible on opened blaze.

and the remains of bearing trees mkd. by Leonard Whitmore, Deputy County Surveyor, in 1962

A hemlock, 9 ins. diam., bears N. 67° E., 16 lks. dist., with healed blaze.

A hemlock, 21 ins. diam., bears S. 10° E., 154 lks. dist., with scribe marks BT visible on partially open blaze.

A hemlock snag, 14 ins. diam., bears West, 108 lks. dist., with healed blaze.

A forked hemlock, 12 ins. diam., bears N. 56° W., 39 lks. dist., with healed blaze.