

December 22, 1981

Page 6
CHAINS

24" hemlock bears N31°E, 28 1/2 links, marked "1/4 SBT" (now a 40" hemlock).
27" hemlock bears N72 1/2°W, 64 links, marked "1/4 SBT" (now a rotted stump).

STATE PARKS CREW FOUND:

A 4" square post.
40" hemlock N30 1/2°E, 20.2' to center, "1/4" visible in blaze, original BT.
28" rotten stump N65°W, 43.0' to center, original BT.

STATE PARKS CREW SET:

5/8"x30" iron rod with aluminum cap marked "OSHD STATE PARKS DIV."
Galvanized steel post with plain white paddle 2.0' south of iron rod.
13" hemlock 21.5' to center S50°W, scribed "1/4 S6BT RS691" and attached yellow Parks corner tag.

WITNESSED BY:

R. Hemmer
S. Doak
M. Swan

1/4 CORNER BETWEEN SECTIONS 1 AND 6

ORIGINAL: 1873

Marked a 8" hemlock for 1/4 section corner.

1892:

On steep mountain side, finding no corner after diligent search, set post 3' long, 3" square, 24" in ground, for 1/4 section corner, marked "1/4 S" on west face from which a:

36" spruce bears N4°W, 57 links, marked "1/4 SBT."
No other trees within limits.

Also make a mound of rocks 4 1/2' at base, 2 1/2' high around the post.

STATE PARKS CREW FOUND:

Nothing.

STATE PARKS CREW SET:

5/8"x30" iron rod with aluminum cap marked "OSHD STATE PARKS DIV."
Galvanized steel post with plain white paddle 2.0' west of iron rod.
18" hemlock S52°E, 35.1' to center, scribed "T3N R10W 1/4 S6BT RS691" and attached yellow Parks corner tag.
77" spruce S70°W, 41.0' to center, blazed but not scribed as wood too rotten to scribe.

WITNESSED BY:

R. Hemmer
L. Boge
S. Doak
M. Swan

WC ON TOWNSHIP LINE 1.75 CHS WEST OF SECTION CORNER 32'33
4

ORIGINAL: 1892

30" hemlock (found to be a spruce) marked: "T4N S33 WC" on NE, "R10W S4" on SE, "T3N S5" on SW and "S32 WC" on NW faces with 4 notches on the east and 2 on the west edges from which a: