

County Surveyor's Record, Tillamook County, Oregon

CHAINS

RESTORED CORNER FOR STATE OF OREGON--DEPARTMENT OF FORESTRY

Witness corner common to Sections 13 and 18, T3N, R8&9W, W.M., Tillamook County, Oregon, (on right bank of Nehalem River.)

ORIGINAL

Basalt stone 20" x 10" x 7"; not found. Point falls near top of 20' cliff, area now covered by log and dirt fill, from which a:

60" Cedar bears S20°E 7 lks.; now 42" stump, found axe work, no scribes visible.

72" Fir bears N58°W 42 lks.; now 42" stump, no evidence of face remaining.

NOTE: Horizontal distances fit very well when measured from the approximate face of BT's.

REWITNESSED by R.A. Morris, RS 401, May 22, 1957 (Recorded in Book 2 Page 355 Tillamook County Surveyors Office).

Mound of stone on East side of MC stone; not found area covered by log and dirt fill, from which a:

6" Cedar bears N86°W 42.8 ft.; now 12", bears N86°W 39.0 ft., face grown over.

14" Alder bears S70°E 39.0 ft.; now 19", bears S70°E 42.8 ft., bark scribes T3N R8W S18 MC BT visible.

4" x 4" x 60" white painted Cedar post bears SE 1.0 ft.; now out of place.

RESTORED

VAR. 21½°E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY WC T3N R9W R8W S13 S18 MC ↓ 1982 RS 1662", 30 inches in ground, in mound of rock, 15.0 ft. North of M.C. stone, and from which a:

29" Fir bears N72°E 82.9 ft. to face; scribed X WC BT.

Rock outcrop bears N55°W 90.0 ft.; chiseled XB0.

South rail of Southern Pacific Railroad bears North 24.0 ft., course S80°E by N80°W.

Set 4" x 4" x 60" white painted Cedar post 2.0 ft. SE of corner pipe. Oregon State Forestry Department metal location poster on 29" Fir BT. Also poster on 60" Cedar original BT.

Dated February 23, 1982.

Restored by David B. Buchholz under my direction.
David B. Buchholz, Transfman

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Loren R. Steele

OREGON
JULY 14, 1978
LOREN R. STEELE
1662

Present and witnessed by Danny J. Benson