

County Surveyor's Record, Tillamook County, Oregon

CHAINS

RESTORED CORNER FOR STATE OF OREGON--DEPARTMENT OF FORESTRY

Section corner common to Sections 9, 10, 15 and 16, T3S, R7W, W.M., Tillamook County, Oregon.

ORIGINAL

Stone 14"x 9"x 6" (now out of place):

Did not mark any bearing trees.

WITNESSED by Frank H. Sharp, June 21, 1894

From above stone, 10"x 10"x 6" marked with 4 notches on South and 3 on East face, (found 3 notches on East) from which a:

- 6" Fir bears N20 $\frac{1}{2}$ °E 78 lks.; missing.
- 5" Fir bears S42 3/4°E 85 lks.; missing.
- 6" Alder bears S52 $\frac{1}{2}$ °W 104 lks.; missing.
- 6" Fir bears N71 3/4°W 61 lks.; missing.

REWITNESSED by Harold J. Russell, RS 707, May 19, 1966 (Recorded in Book 3, Page 44, Tillamook County Surveyors Office).

From above stone, marked "X" in top, (found) and from which a:

- 14" Fir bears S49 $\frac{1}{4}$ °E 12.0 ft.; now 14", face grown over.
- 19" Fir bears N55°E 12.6 ft.; now 17", face grown over.
- 21" Fir bears N17 3/4°W 9.4 ft.; now 23" snag, 20 ft. tall, face grown over.
- 23" Fir bears S62°W 24.1 ft.; now 24" stump, 4 ft. tall, cut above closed face.

RESTORED

Var. 21 1/2° E
DRB 9/16/82

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T3S, R7W, S9 S10 S16 S15 1982 RS 1998", 34 inches in ground, original stone deposited N20°E 0.7 ft., to "X", from pipe, and from which a:

- 31" Fir bears N76°W 23.1 ft. to face; scribed T3S, R7W, S9 BT.
- 4" x 4" x 40" white painted Cedar post SW 1.0 ft. from corner pipe.
- Oregon State Forestry Department metal location poster on 21" fir BT. Also BLM poster on all of Russell's BT's.

Dated: July 30, 1982.

Restored by David B. Buchholz under my direction.
David B. Buchholz, Transitman

REGISTERED
PROFESSIONAL
AND SURVEYOR

Anthony J. Klosterman
OREGON
JULY 16, 1982
ANTHONY J. KLOSTERMAN
1998

Present and witnessed by Danny J. Benson