

ENTRY NO. 174: 11 October 1982 Remonumenting the township corner common to Townships 3 and 4 North, Ranges 5 and 6 West, W.M., from Government Bearing Trees.

- Record no. 1: Government Notes of Range line by John Campbell, Deputy Surveyor - January 24, 1877
"Set post of hemlock 5 inches square for corners to towns 3 and 4 North of Ranges five and six west of Willamette Meridian from which is
a Fir tree 24 in. dia. bears N 80° E 20 links (13.20 feet)
a Hemlock 6 in. dia. bears S 45° E 34 links (22.44 feet)
a Fir 50 in. dia. bears S 45° W 60 links (39.60 feet)
a Fir 40 in. dia. bears N 45° W 20 links" (13.20 feet)
- Record no. 2: Government Resurvey of north boundary of 3N5 by John Campbell, Deputy Surveyor - July 28, 1880
"to the post at the corner to Townships 3 and 4 North Ranges 5 and 6 West"
- Record no. 3: Government Notes by L.E. Wilkes, Deputy Surveyor - Sept. 10, 1892
"a point from which the corner to Tps 3 & 4 N Rs 5 & 6 W bears west 13 lks dist.
This corner is marked by an old stake badly decayed and marks not all legible. Also a stake more recently set. Marked T4N S 31 on N.E.; R5W S6 on S.E.; T3N, S1 on S.W.; R6W S36 on NW faces with 6 notches in each edge, from which
a Fir 24 ins diam bears N 52° E 20 lks dist (13.20 feet)
Marked T4N R5W S31 B.T.
a hemlock 6 ins diam bears S 74°30' E 29 lks dist (19.14 feet)
Marked T.3 N5
a Fir 20 ins diam bears S 39° E 33 lks dist (21.78 feet)
Marked T3N R5W S6 B.T.
a Fir 40 ins diam bears S 27° W 47 lks dist (31.02 feet)
Marks in bark and not legible
a Fir 40 ins diam bears N 73° W 20 lks dist (13.20 feet)
Marked T4N R6W S 36 B.T."
- Record no. 4: Oregon State Highway Department map. 4B16-2, 'TILLAMOOK COUNTY LINE - SUNSET CAMP SECTION of WOLF CREEK HIGHWAY' - Nov., 1932
"Cor. found"
- Record no. 5: Survey no. 3231 by A.V. Benedict, Oregon State Highway Engineer - Surveyed from Sept. 24, 1940 to Dec. 18, 1940*
*"Setting all permanent markers was not completed until the following summer and the map was not completed until December, 1942.
The corner to townships 3 and 4., of Ranges 5 and 6 W., W.M. This is a 1 1/2" iron pipe, from which a 24" fir bears N.80°E. 13 ft., and a 40" fir bears N.45°W. 13 ft. This latter tree uprooted and both burned, with barely discernable scribing. We replace the pipe with a concrete pedestal 12" square at top, 18" square at bottom and 36" high, set 36 inches in the ground, with 2 1/2" brass disc on which is stamped a cross and the numbers 36-31-1-6 and circumferentially, SEC. COR. TPS 3 & 4N. RGS. 5 & 6W. W.M. - O.S.H.D. We also set two 4" x 4" white guard posts, one stenciled SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces and the other stenciled CLATSOP COUNTY, COLUMBIA COUNTY, WASHINGTON COUNTY and TILLAMOOK COUNTY' on the respective faces in black. No live trees available for bearing trees."
- Record no. 6: Survey no. 7221 by C.R. Miller - 1955 (approx.)
"Section corner 36 31 T.4 North Range 5 and 6 West.
1 6 T.3 North Range 5 and 6 West
We find a 1 1/2" x 3' iron pipe and white post for section corner and white post for county corner. A 37" fir with a burned out face but no visible scribe bears N 86° W 38.0 feet. No other B.T. is evident"

Found brass disk sitting in concrete as set in Survey no. 3231. A badly rotted 2 foot Fir log was partially laying over said disk. A 2" outside diameter (O.D.) x 53" long, rusted iron pipe, the lower end of which had been pointed, was leaning against said log. A rotted off, 4" square, wooden post (painted white), marked "SEC COR"