

Found a squared off limb 13.0' S55°E from our corner. No scribes on limb.

Witnessed by: R. Hemmer
L. Boge
L. Hetteema

S $\frac{1}{4}$ Section 31, T4N R10W W.M.

Original: 1892 - $\frac{1}{4}$ Corner 31 & 6

Set post 4' long, 4" square, 24" in ground, for $\frac{1}{4}$ section corner and marked " $\frac{1}{4}$ S" on north face from which a

12" hemlock bears N22°W, 47 links, marked " $\frac{1}{4}$ SBT"
10" hemlock bears S44°E, 21 links, marked " $\frac{1}{4}$ SBT"

State Parks Crew found:

2 $\frac{1}{2}$ " iron pipe set by Crown Zellerbach with 3" cap marked T4N R10W $\frac{1}{4}$ 31
1973 RS954"
4"x4" white post 3.0' high, 1.5' east of iron pipe
18" hemlock S20°W, 29.4' to center with scar painted over with
fluorescent red paint (did not chop out)
26" hemlock, rotted stump, S48°E, 16.0' to center, with old scar
and red fluorescent paint. Trace of scribe visible.

State Parks Crew Set:

Galvanized steel post with paddle marked "OREGON STATE PARK BOUNDARY DO NOT DISTURB" 2.0' NW of iron pipe.

Witnessed by: R. Hemmer
S. Doak

Corner Information from June 1982 Survey
Var. 20 $\frac{1}{2}$ °

Center $\frac{1}{4}$ Corner Section 31

Original: Set by Robert A. Hovden for Crown Zellerbach

State Parks Crew Found:

2" iron pipe with brass cap set in concrete with Crown Z emblem and
"RS954" marked on cap
a 23" hemlock stump 13.7' west marked "C $\frac{1}{4}$ S31BT RS954"
a 31" hemlock stump 39.7', S31°E tagged and marked "C $\frac{1}{4}$ S31BT"
tag dated 1973
a white 4"x4" witness post 3.5 feet north sharpened, rammed and
wedged into a 4 foot diameter log

Parks Crew Set:

Galvanized steel post with paddle marked "OREGON STATE PARK BOUNDARY DO NOT DISTURB" 2.0 feet west of iron pipe

Witnessed by L. Doss
R. Depuy
C. Middleton