

RESTORED CORNER FOR STATE OF OREGON -- DEPARTMENT OF FORESTRY

Line Tree common to Sections 19 and 20, T3N, R7W, W.M., Tillamook County, Oregon.

ORIGINAL

82" fir line tree; now a 82" stump with old hack marks on North side.  
Stump cut to low for marks on South side. This is the only 82" fir in the area.

2 lk. brook bears South 209.88', crs., N.E.; in place.  
Top of Spur bears South 345.18', slopes N.E.; in place.  
1/4 corner 19 and 20 section corner 17, 18, 19, and 20 1/4 corner 17 and 18 to the North are missing.  
Top of ridge bears  $N0^{\circ} 5'W$  6753.12' course East and West; in place.

RESTORED

VAR 21  $1/2^{\circ} E$

Set 5/8" x 30" iron rod with yellow plastic cap marked PLS 1662 30" into the center of the 82" fir stump, and from which a:

9" Alder bears  $S2^{\circ}E$  7.1 ft. to face; bark scribed WPS20BT.  
9" Alder bears  $N37^{\circ}W$  4.5 ft. to face; bark scribed WPS19BT.

Set 4" x 4" x 60" white painted Cedar post SE 1.5 ft. from iron rod.  
Oregon State Forestry Department metal location on poster on 9" Alder  $S2^{\circ}E$  7.1 ft. BT.

Dated October 30, 1985.

Restored by \_\_\_\_\_



Present and witnessed by S. Ellis  
O Hendrick

