

RESTORED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

One quarter corner common to Sections 20 and 21, T1N, R7W, W.M., Tillamook, Oregon.

ORIGINAL by Henry Meldrum, September 22, 1884.

Post on ridge top, course N65°W; missing.

21" Hemlock bears N26°W 13 lks.; missing.

28" Fir bears N44°E 29 lks.; now a 44" stump with portions of scribes visible.

NOTE: Distance measured to center of BT.

RESTORATION by Lyle E. Byers LS 199, March 19, 1951, (Book 2, Page 64, Tillamook Co. Records).

Corner point fell in road, from which a:

1 1/2" X 36" galvanized iron pipe with 3" bronze cap bears North 15.0 ft.; now in place.

42" Fir stub bears S40°W 23.5 ft.; now a 28" badly rotted stub with no scribes visible, bears S46°W 24.5 ft.

58" Fir stump bears N41°W 33.7 ft.; now a 56" stump with scribes 1/4 S20 BT 199 visible, bears N45°W.

NOTE: Distance measured to face of BTs.

RESTORED

Var. 21 1/2° E

Set 1 1/2" X 30" aluminum pipe with 3 3/4" cap marked "STATE OF OREGON DEPARTMENT OF FORESTRY T1N R7W 1/4 S20 S21 1987 LS1998", 30 inches in ground, and from which a:

13" Fir bears N16°E 10.9 ft. to face; scribed 1/4S21BT.


16" Fir bears N62°W 34.1 ft. to face; scribed 1/4S20BT.

Metal location poster on new BTs.


Also poster on 28" original BT.

Dated April 2, 1987.

Restored by



*Anthony J. Klosterman*



Present and witnessed by David B. Buchholz  
Clifford R. Foster