

REWITNESSED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

Section corner common to Sections 5, 6, 7 and 8, T2N, R7W, W.M.,
Tillamook County, Oregon.

ORIGINAL By Henry Meldrum, August 1, 1893.

15"x11"x7" basalt stone with 5 notches on East and South edges;
found alongside pipe.

- 22" Hemlock bears N54°E 64 lks.; now a 36" stump, upper face
burnt out, with portions of scribes visible on lower face.
- 40" Hemlock bears S44°E 41 lks.; now a 52" badly rotted stump
with portions of scribes visible. Distance 29.6 ft.
- 14" Hemlock bears S62°W 47 lks.; now a 18" badly rotted stump
with axe work visible on burnt and rotted face.
- 30" Hemlock bears N47°W 62 lks.; now a 48" badly rotted stump
with portions of scribes visible on burnt out face.

RESTORATION by Louis W. Amort, RE2311, August 18, 1952 (Book 2, page
187, Tillamook County Records).

1 1/2"x36" galvanized iron pipe with 3" bronze cap, 28" in ground,
in mound of rock; in place.

- 48" Fir stump bears N63°E 44.2 ft.; now 48", badly rotted,
with portions of scribes 2N R7W S5 BT visible.
- 52" Fir stump bears S13°E 87.4 ft.; now 52", badly rotted,
with portions of scribes T2N R7W S8 BT visible.
- 36" Fir stump bears S69°W 27.1 ft.; now 36", with scribes
T2N R7W S7 BT RE2311 visible.

REWITNESSED

Var 21 1/2°E

From above pipe with marks "1987 LS1998" added, and from which a:

- 12" Fir bears S52°E 16.1 ft. to face; scribed T2NR7WS8BT.
- 15" Fir bears N72°E 26.8 ft. to face; scribed T2NR7WS5BT.
- 11" Fir bears S32°W 8.5 ft. to face; scribed T2NR7WS7BT.
- 8" Hemlock bears N63°W 15.6 ft. to face; scribed T2NR7WS6BT.


4"x4"x60" white painted Cedar post S52°E 1.5 ft. from corner pipe.
Metal location poster on new BTs.

Dated May 20, 1987.

Rewitnessed by



Anthony J. Klosterman



Present and witnessed by David B. Buchholz
Clifford R. Foster

BOOK 6

822