

REWITNESSED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

One quarter corner common to Sections 5 and 8, T2N, R7W, W.M.,
Tillamook County, Oregon.

ORIGINAL by Henry Meldrum, August 1, 1893.

17"x14"x9" basalt stone 11" in ground with 1/4 on north face;
in place.

15" Hemlock bears S35W 59 lks.; now a 20"x5 ft. high badly
rotted stub with portions of scribes visible.

16" Hemlock bears N47W 16 lks.; missing.

REWITNESSED by Louis W. Amort RE2311, October 6, 1953 (Book 2, page
300, Tillamook County Records).

1 1/2"x36" galvanized iron pipe with 3" bronze cap, 30" in ground,
in mound of rock, on south side of stone; in place.

60" Fir snag bears N68E 45.8 ft.; now a 60" stump with
portions of scribes R2311 visible on badly rotted face.

74" Fir stump bears S69 1/2W 39.4 ft.; now 74" with portions of
scribes visible on badly rotted face.

REWITNESSED May 20, 1988

Var. 21 1/2 E

From the above stone with an "X" added and also added marks "LS1998
1988" to pipe, and from which a:

15" Fir bears N03E 18.2 ft. to face; scribed 1/4S5BT.

21" Fir bears N77W 34.4 ft. to face; scribed 1/4S5BT.


11" Hemlock bears S52E 9.1 ft. to face; scribed 1/4S8BT.

Metal location poster on new BTs.

3/4" brass washer marked "LS1998" nailed to face of new BTs.

Present and witnessed by David B. Buchholz and Clifford R. Foster.

Rewitnessed by



Anthony J. Klosterman

