

REWITNESSED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

One quarter corner common to Sections 17 and 20, T1N, R7W, W.M.,
Tillamook County, Oregon.

ORIGINAL by Henry Meldrum, September 27, 1884.

Post; missing.

44" Fir bears N25E 26 lks.; now a 68" stump, no face visible.
46" Fir bears S48E 34 lks.; now a 62" stump, no face visible.

RESTORED by W.E. Anderson, county surveyor, January 6, 1932. (Book 4
page 38, Tillamook County Records).

Fir limb; missing.

60" Fir (original) bears S48E 22.4 ft.; now a 62" stump, no
scribes visible on burnt out face. (Rescribed in 1932)

RESTORED By Lyle E. Byers LS199, February 28, 1951. (Book 2 page 66A,
Tillamook County Records).

1 1/2"x36" galvanized iron pipe with 3" bronze cap; in place, 32"
in ground.

64" Fir stump bears S83E 40.0 ft.; now 64" with scribes 1/4"
S20 BT 199 visible.

REWITNESSED June 23, 1988

Var 21 1/2 E

From above pipe with marks "1988 LS1998" added and from which a:

11" Fir bears S02E 52.7 ft. to face; scribed 1/4S20BT.
13" Fir bears N09E 70.7 ft. to face; scribed 1/4S17BT.

Metal location poster on new BTs.

Also 1951 metal location poster on 60" Fir BT S48E 22.4 ft.

3/4" brass washer marked "LS1998" nailed to face of new BTs.

Present and witnessed by David B. Buchholz and Clifford R. Foster.

Rewitnessed by

