

REWITNESSED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

One quarter corner common to Sections 5 and 6, T3S, R7W, W.M.,
Tillamook County, Oregon.

ORIGINAL by Frank H. Sharp, June 30, 1894.

Post; missing.

12" Hemlock bears N20E 40 lks.; now root crown, in place.
10" Hemlock bears N63W 12 lks.; missing.

RESTORATION by Louis W. Amort RE2311, November 12, 1953 (Book 2,
page 315 Tillamook Co. Records.)

1 1/2"x36" galvanized iron pipe with 3" bronze cap, 30" in
ground, in mound of stone; in place.

16" Fir snag bears S85W 29.5 ft.; now a 16" stump with
scribes 1/4 S6 BT visible.

42" Fir snag bears N71E 58.2 ft.; now a 42" stump with
scribes 1/4 S5 BT RE2311 visible.

4"x4"x48" white painted Cedar post 1.0 ft. North of pipe;
in place.

REWITNESSED July 14, 1988

Var. 21 1/2 E

From above pipe with marks "LS1998 1988" added, and from which
a:

19" Fir bears N25W 19.4 ft. to face; scribed 1/4S6BT.

10" Fir bears N20E 35.1 ft. to face; scribed 1/4S5BT.


Metal location poster on new BTs.

1953 O.S.B.F. and 1955 B.L.M. metal location posters on 42" Fir
stump bears N71E 58.2 ft.

3/4" brass washer marked "LS1998" nailed to face of new BTs.

Present and witnessed by David B. Buchholz and Clifford R. Foster.

Rewitnessed by



Anthony J. Klosterman

