

REWITNESSED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY

Section corner common to Sections 20, 21, 28 and 29, T1N, R8W,
W.M., Tillamook County, Oregon.

ORIGINAL by Henry Meldrum, August 23, 1884.

Post; missing.

- 12" Hemlock bears N46W 37 lks.; Now a badly rotted 2 ft.
high stub with axe work visible.
- 8" Hemlock bears N21E 36 lks.; missing.
- 5" Hemlock bears S61E 23 lks.; missing.
- 4" Hemlock bears S39W 75 lks.; missing.

RESTORATION by Louis W. Amort RE2311, August 22, 1952 (Book 2,
page 180, Tillamook County Records).

1 1/2"x36" galvanized iron pipe with 3" bronze cap, 30" in
ground, in large mound of stone; in place.

54" Fir stump bears N50W 71.4 ft.; now a 54" badly rotted
stump with scribes T1N R8W S20 BT visible.

48" Fir snag bears N29E 60.0 ft.; now 48" badly rotted,
face with scribing visible has fallen off and is
laying alongside.

10'x15'x20' high rock outcrop bears S11 1/2E 180.0 ft. (no
marks); in place.

REWITNESSED August 30, 1988

Var. 21 1/2 E

From the above pipe with marks "LS1998 1988" added, and from
which a:

13" Fir bears N52 1/2E 7.5 ft. to face; scribed T1NR8W
S21BT.

8" Fir bears N61W 23.9 ft. to face; scribed T1NR8WS20BT.

7" Fir bears S25E 10.4 ft. to face; scribed T1NR8WS28BT.

9" Fir bears S74W 22.4 ft. to face; scribed T1NR8WS29BT.

Metal location poster on new BTs.

Also metal location poster on 48" Fir snag BT N29E 60.0 ft.

3/4" brass washer marked "LS1998" nailed to face of new BTs.

Present and witnessed by David B. Buchholz and Clifford R. Foster.

Rewitnessed by

