

TILLAMOOK COUNTY SURVEYORS OFFICE

SE 1/16 corner of Section 8 T.5S.,R.10W.,W.M.

Government lots 18,19,30, & 31



I set a 1 1/2" iron pipe with a 3" brass cap at the found position of the original stone marked "XVI" and encased in a 10" concrete cylinder.

History of Found Monument

This corner was originally set J.W. Meldrum, deputy surveyor under contract No. 166 dated Jan. 10, 1872, (See Tillamook County Surveyors G.L.O. book 5S10 page 23), set stone 12X12X8. I found a 12X11X7 stone marked "XVI" 6.0' North of an old E-W fence line in the roots of a 60" spruce stump.

New Accessories

- *72" light hat section post South 6.0' in an old E-W fence line.
- *62" spruce S.67*E. 51.51' scribed SE1/16S8B.TCS.
- *15" alder N.2*W. 6.25' scribed SE1/16S8B.TCS.

The distances were measured to a finish nail with a Tillamook County Surveyors Brass Washer between the scribed B and the T.

*indicates yellow Tillamook County location poster attached.


Monument location

This monument is located 9' East of a 3' wide creek course N.32*E. and 39' West of a 1' wide creek course N.28*W. I laid the found stone on the West side of the monument. The corner is on the North side of a 60" spruce stump and the fence jogs around the South side of the stump.

In the presence of Dan McNutt, & Al Dvorak

September 20 1990

Title:



Allan E. Duncan, C.S.

