

RESTORED CORNER FOR THE OREGON DEPARTMENT OF FORESTRY
4907 Third St., Tillamook, Oregon 97141

Section corner common to Sections 5, 6, 7 and 8, T2N, R8W, W.M.,
Tillamook County, Oregon.

ORIGINAL by Henry Meldrum, August 18, 1893.

17"x10"x6" Basalt stone, 11" in ground with 5 notches on South
and East edges; found stone with marks on South and East
sides, in place.

- 18" Hemlock bears N41E 48 lks.; missing.
- 20" Hemlock bears S46E 17 lks.; now a 12"x4 foot high badly
burnt and rotted stub with no scribes visible.
- 12" Hemlock bears S37W 6 lks.; missing.
- 14" Hemlock bears N20W 46 lks.; missing.

REWITNESSED by Louis W. Amort RE2311 December 17, 1954 (Book 1,
page 165, Tillamook County Records).

Erected mound of stone around corner stone; in place.

- 50" Fir snag bears N59E 25.7 ft.; now a 5 ft. high badly
rotted stump with scribes T2N R8W S5 BT visible.
 - 4" Alder bears N06W 13.3 ft.; now 15" with faint X, no
other scribes visible.
 - 60" Cedar stump bears S58W 71.7 ft.; now 5 ft. high badly
rotted with scribes T2N R8W S7 BT RE visible.
 - 4" Alder bears S23E 9.9 ft.; now 12" with scribes X BT in
poor condition very low on tree.
- Found 4"x5"x60" white painted Cedar post 1.7 ft. NW of
corner stone.

RESTORED October 21, 1991

Var. 19 1/2E

Set 1 1/2"x30" Aluminum pipe with 3 3/4" cap marked "STATE OF
OREGON DEPARTMENT OF FORESTRY T2N R8W S6 S5 S7 S8 1991 LS1998",
28" in ground, in mound of stone, original stone placed at NW
edge of pipe, and from which a:

- 14" Fir bears N43W 27.4 ft. to face; scribed T2NR8WS6BT.
- 15" Alder bears S23 1/2W 35.2 ft. to barkscribes
T2NR8WS7BT.
- 3/4" brass washer marked "LS1998" nailed to Amorts NW Bt
bears N04 1/2W 12.7 ft.
- 3/4" brass washer marked "LS1998" nailed to Amorts SE Bt
bears S26 1/4W 9.45 ft.

Metal location poster on new Bts and Amorts Alder Bts.
3/4" brass washer marked "LS1998" nailed to face of new Fir Bt.
Present and witnessed by Clifford R. Foster.

Restored by David B. Buchholz under my direction.
David B. Buchholz, LS2272

