

TOWNSHIP CORNER COMMON TO THE NORTHEAST CORNER OF TOWNSHIP 3 NORTH,
RANGE 7 WEST AND TO THE SOUTHEAST CORNER OF TOWNSHIP 4 NORTH, RANGE
7 WEST, WILLAMETTE MERIDIAN.

HISTORY:

Record No. 1 November 16, 1891 - Henry Meldrum, GLO Deputy Surveyor in survey of the East boundary of T3N, R7W; North between 1-6 ...80.00 Set post 4-1/2 ft long 4 ins Sq 24 ins in ground for corner to Townships 3 and 4 North Ranges 6 and 7 West, from which:
Book 30 Page 514
A 12" Hemlock bears N72°E, 58 lks. (38.20');
A 20" Hemlock bears S33°E, 42 lks. (27.72', Note: Meldrum visits this corner later and calls the distance to this witness as 45 lks. = 29.70');
A 30" Hemlock bears S38°W, 17 lks. (11.22');
A 24" Hemlock bears N47°W, 34 lks. (22.44').

Record No. 2 May 20, 1892 - John McQuinn, GLO Deputy Surveyor in survey of the East boundary of T4N, R6W;
"I begin at the Cor. to Townships 3 and 4 North Ranges 6 and 7 West which is a post 4 ins. square firmly set in the ground [McQuinn finds the witnesses as called by Meldrum in Record No. 1]."

Record No. 3 June 19, 1893 - Lincoln E. Wilkes, GLO Deputy Surveyor in survey of East line of T3N R6W; North retracing the range line on the West boundary of Section 6.
Book 30 Page 97
50.60 to a point from which the corner as established for corner to Townships 3&4 North, Ranges 6&7 West ... from which:
An 18" Hemlock bears N72°E, 58 lks. (38.28');
A 24" Hemlock bears S33°E, 45 lks. (29.70');
A 36" Hemlock bears S38°W, 18 lks. (11.88');
A 24" Hemlock bears N47°W, 34 lks. (22.44').
After destroying all marks on bearing trees and stake which refer to sections 31 and 6.
73.85 the closing corner to Townships 3 and 4 North Range 6 West which is marked by a hemlock 6 ins diam."

Record No. 4 February 21, 1955 - Louis W. Amort, Oregon Engineer No.2311; "ORIGINAL Post, now missing, found rotted stake point in place from which a: [Calls to GLO bearing trees as follows]
Book 1 Page 100
SW BT = "now 31" stump, face and scribes burnt out."
NW BT = "now 36" stump, scribes S36 visible, rest unexposed."
"RESTORED Set 1-1/2" X 36" galvanized iron pipe with 3" bronze cap marked 'OREGON STATE BOARD OF FORESTRY T4N T3N R7W R6W S36 S6 S1 T3N 1955 RE2311," 32 inches in ground, in mound of stone, and from which a:
55" Fir stump bears S9-1/2°W 118.8 ft.; scribed T3N R7W S1 BT.
36" Fir stump bears N83°W 59.1 ft.; scribed T4N R7W S36 BT RE 2311.
Set 4" X 4" X 50" white Cedar post 2'E. of pipe. Oregon State Board of Forestry metal location poster on 36" Fir stump BT. Oregon State Board of Forestry metal location poster on 4" X 4" X 50" white Cedar post on N edge road, approx. 260' S." (Bearing Tree Book page 199-6, Clatsop County survey Records.)



Record No. 5 August, 1987 - George Ford, Oregon Land Surveyor No. 2210; "FOUND 1-1/2" IRON PIPE
36" HEMLOCK STUMP (GLO) N44°W AT 24.0 FT. I.P.CO. TAG.
24" HEMLOCK STUMP (GLO) S40°W AT 12.1 FT.
SET REBAR WITH CAP NEXT TO PIPE. R.P. ED:
4" FIR N3°E AT 10.4 FT.
14" FIR EAST AT 7.0 FT.
5" FIR S8°W AT 7.2 FT.
(County Survey No. B-8627, Clatsop County Survey Records.)