

**TILLAMOOK COUNTY SURVEYORS OFFICE
COURTHOUSE, TILLAMOOK, OREGON 97141**

**SECTION CORNER COMMON TO SECTIONS 24 AND 25, T.2 N.,
R.10 W. AND SECTIONS 19 AND 30, T.2 N., R.9 W., W. M.**

**I FOUND AN OREGON STATE BOARD OF FORESTRY IRON PIPE AND BRASS CAP,
STAMPED AS SHOWN HEREON. I ENCASED THE FOUND MONUMENT IN A 10"
DIAMETER CONCRETE CYLINDER AND A MOUND OF STONES.**

**T2N
R10W | R9W
S24 S19
S25 S30
1954
RE 2311**

HISTORY OF FOUND MONUMENT

**THE MONUMENT WAS FOUND AS DESCRIBED IN REWITNESS BOOK 1, PAGE 107,
AND THE ACCESSORIES FOUND AND/OR SET AT THAT TIME TO NOW BE AS
FOLLOWS:**

**REWITNESS BOOK 1, PAGE 107, SET A 1-½" X 36" GALVANIZED IRON PIPE WITH
3" BRONZE CAP MARKED "OREGON STATE BOARD OF FORESTRY T2N R10W
R9W S19 S30 S24 S25 1954 RE 2311", 32 INCHES IN GROUND AND SET OVER THE
TOP OF A ½" X 43" PIPE (SET BY W. A. MARKHAM RE 1842 IN 1949) MOVED TO
THE TRUE CORNER POINT BY CONSENT OF COUNTY SURVEYOR AND W.A.
MARKHAM IN 1954.**

**REWITNESS BOOK 1, PAGE 107, A 30" DIAMETER FIR BEARING SOUTH 77° WEST
28.1' SCRIBED "S25 BT"; 08-31-05 FOUND A 20" DIAMETER ROTTEN AND BURNT
STUB, 25' TALL AT RECORD POSITION, NO MARKS VISIBLE.**

*** REWITNESS BOOK 1, PAGE 107, A 30" DIAMETER FIR BEARING NORTH 20°
WEST 26.0' SCRIBED "T2N R10W S24 BT RE 2311"; 08-31-05 FOUND A 38" DIAMETER
FIR WITH HEALED FACE BEARING NORTH 20° WEST 26.9'. DISTANCE WAS
MEASURED TO THE FACE OF THE METAL LOCATION POSTER.**

**REWITNESS BOOK 1, PAGE 107, A 14" DIAMETER FIR BEARING SOUTH 52° EAST
22.0' SCRIBED "T2N R9W S30 BT"; 08-31-05 FOUND A 13" DIAMETER HIGH STUMP,
NO BARK REMAINING, 10' TALL AT RECORD POSITION, NO MARKS VISIBLE.**

**REWITNESS BOOK 1, PAGE 107, A 20" DIAMETER FIR BEARING NORTH 37° EAST
40.0' SCRIBED "T2N R9W S19 BT"; 08-31-05 FOUND A 18" DIAMETER BURNT STUMP
WITH BACK HALF OF TREE MISSING, 8' TALL AT RECORD POSITION, NO MARKS
VISIBLE.**

**REWITNESS BOOK 1, PAGE 107, A 5" DIAMETER HEMLOCK WITH OREGON
STATE BOARD OF FORESTRY METAL LOCATION POSTER BEARING NORTH 69°
WEST 20.1'; 08-31-05 FOUND A DOWN AND ROTTEN HEMLOCK TREE, NO METAL
LOCATION POSTER VISIBLE.**

**REWITNESS BOOK 1, PAGE 107, SET A 4" X 4" X 72" WHITE CEDAR POST 1.0' NW
OF PIPE. 08-31-05 FOUND A SPLIT CEDAR FENCE POST WITH SCRIBE MARKS
VISIBLE, ROTTED AT BOTTOM AND REPLACED AT RECORD POSITION.**

SURVEYS AND REWITNESSES OF RECORD

A-1208	OCTOBER 1964	JOHN L. CARLICH	LS 287
F-40-86	NOVEMBER 1949	W.A. MARKHAM	RE 1842
B-565	JULY 1968	HAROLD J. RUSSEL	LS707

G.L.O. ORIGINAL, JULY 17, 1873, BLM MICROFILM VOLUME R122 AND TRANSCRIBED IN G.L.O. BOOK 1, PAGE 14, TILLAMOOK COUNTY SURVEY RECORDS.

REWITNESS BOOK 1, PAGE 107 LOUIS W. AMORT RE 2311

NEW ACCESSORIES

*36" DIAMETER DOUGLAS FIR TREE BEARING SOUTH 48° WEST 26.3' SCRIBED "T2NR10WS25BTCS". DISTANCE WAS MEASURED TO A BRASS WASHER STAMPED "T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

*6" DIAMETER DOUGLAS FIR TREE BEARING NORTH 37° EAST 18.7' SCRIBED "S19BT". DISTANCE WAS MEASURED TO A BRASS WASHER STAMPED "T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

*5" DIAMETER DOUGLAS FIR TREE BEARING SOUTH 11° EAST 24.3' SCRIBED "S30BT". DISTANCE WAS MEASURED TO A BRASS WASHER STAMPED "T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

*SET 72" LIGHT HAT SECTION POST SOUTH 3.0' FROM MONUMENT.

* INDICATES TILLAMOOK COUNTY YELLOW METAL LOCATION POSTER ATTACHED.

LOCATION OF MONUMENT

THIS SECTION CORNER IS LOCATED APPROXIMATELY 200' SOUTH OF AN OLD LOGGING LANDING.

IN THE PRESENCE OF, AND REWITNESSED BY DANNY R. MCNUTT, TILLAMOOK COUNTY SURVEYOR AND JOE JENSEN, SURVEY SUPERVISOR, TILLAMOOK COUNTY SURVEYOR'S OFFICE.

SEPTEMBER 02, 2005

TITLE:

