

**TILLAMOOK COUNTY SURVEYORS OFFICE  
COURTHOUSE, TILLAMOOK, OREGON 97141**

**ONE-QUARTER CORNER COMMON TO SECTIONS 15, AND 16, TOWNSHIP 1  
NORTH, RANGE 10 WEST, WILLAMETTE MERIDIAN, TILLAMOOK COUNTY,  
OREGON.**

**I FOUND A 3" DIAMETER BRASS CAP IN GOOD CONDITION STAMPED AS SHOWN  
HEREON. I ENCASED THE MONUMENT IN A CONCRETE CYLINDER.**



---

**HISTORY OF FOUND MONUMENT**

**THIS MONUMENT WAS ORIGINALLY SET BY THE GENERAL LAND OFFICE BY C.  
HANDLEY IN JULY OF 1873. THE CORNER WAS THEN REESTABLISHED BY  
RICHARD A. MORRIS, L.S. 401 IN SEPTEMBER OF 1964 AND FILED AS MAP A-1206,  
TILLAMOOK COUNTY SURVEY RECORDS.**

**THE MONUMENT WAS FOUND AS DESCRIBED ON MAP A-1206, AND THE  
ACCESSORIES FOUND AND/OR SET AT THAT TIME TO NOW BE AS FOLLOWS:**

**MAP A-1206, SET A 9" DIAMETER HEMLOCK WHICH BEARS SOUTH 83 1/2° EAST  
17.6'; 12-15-05 BEARING TREE IS NOW GONE.**

**MAP A-1206, SET AN 18" DIAMETER HEMLOCK WHICH BEARS SOUTH 56° WEST  
28.8'; 12-15-05 FOUND A TREE LYING ON GROUND.**

**MAP A-1206, FOUND A 2-1/2" IRON PIPE WHICH BEARS NORTH 52° 37' WEST 267.3';  
12-15-05 FOUND AT RECORD POSITION.**

**MAP A-1206, SET A 4" X 4" X 52" WHITE PAINTED CEDAR POST 1.0' NORTHWEST  
OF MONUMENT; 12-15-05 FOUND A ROTTEN WHITE POST LYING ON THE  
GROUND NEXT TO THE MONUMENT.**

**MAP A-1206, SET AN OREGON STATE BOARD OF FORESTRY METAL LOCATION  
POSTER ON 18" DIAMETER HEMLOCK BEARING TREE; 12-15-05 METAL POSTER  
TAG IS NOW GONE.**

---

**SURVEYS AND REWITNESSES OF RECORD**

**G.L.O. Contract Surveyed by C. Handley, July 10, 1873.**

**G.L.O. BOOK 1N&2N, PAGES 42-43, Tillamook County Survey Records.**

**MAP A-1206, Richard A. Morris, L.S. 401, September 1964**

**MAP A-1673, Harold J. Russell, L.S. 707, January 1968**

---

**NEW ACCESSORIES**

**\*15" DIAMETER DOUGLAS FIR TREE WHICH BEARS SOUTH 44° WEST 16.8'  
SCRIBED "TINR10WS16BT". DISTANCE WAS MEASURED TO A BRASS WASHER  
STAMPED "T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.**

\*15" DIAMETER DOUGLAS FIR TREE WHICH BEARS NORTH 48° WEST 31.87'  
SCRIBED "TINR10W1/4S16BT". DISTANCE WAS MEASURED TO A BRASS WASHER  
STAMPED "T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

\*19" DIAMETER DOUGLAS FIR TREE WHICH BEARS NORTH 68° EAST 17.1'  
SCRIBED "TINR10W1/4S15BT". DISTANCE WAS MEASURED TO A BRASS WASHER  
STAMPED "T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

BASIS OF BEARINGS FOR BEARING TREES IS MAGNETIC.

\*SET 72" LIGHT HAT SECTION POST SOUTH 2.0' FROM MONUMENT.

SET STEEL FENCE POST EAST 3.7' FROM MONUMENT.

\* INDICATES TILLAMOOK COUNTY YELLOW METAL LOCATION POSTER  
ATTACHED.

---

LOCATION OF MONUMENT

THIS SECTION CORNER IS LOCATED ON A STEEP SLOPE APPROXIMATELY 50'  
SOUTH OF AN OLD LOGGING ROAD.


NOTE: NO ATTEMPT WAS MADE TO VERIFY THE POSITION OF THIS MOMUMENT  
FROM THE INFORMATION CONTAINED ON SURVEY MAP A-1206. THE INTENT OF  
THIS REWITNESS/RESTORATION IS TO PERPETUATE THE POSITION AS  
PREVIOUSLY ESTABLISHED BY SAID SURVEY MAP .

IN THE PRESENCE OF, AND REWITNESSED BY DANNY R. MCNUTT, TILLAMOOK  
COUNTY SURVEYOR AND JOE JENSEN, SURVEY SUPERVISOR, TILLAMOOK  
COUNTY SURVEYOR'S OFFICE.


---

DECEMBER 15, 2005

TITLE:



*Danny R. McNutt C.S.*



RENEWAL12-31-2006

