

Index

CORNER RECORD (SEARCH)

File No. H-23 PROJ. NO. Panther #2 CORNER CS 1/16
 TOWNS. 6S RANGE 10W R.D. Hebo COUNTY Tillamook GCDB# 640520
 MERID. W.M. FOREST Siuslaw STATE Oregon

<p>CORNER DIAGRAM</p> <p>N ↑</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="width:50px; height:50px; text-align:center;">S</td> <td style="width:50px; height:50px; text-align:center;">12</td> </tr> <tr> <td style="text-align:center;">Center</td> <td style="text-align:center;">South</td> </tr> <tr> <td colspan="2" style="text-align:center;">● 1/16</td> </tr> </table>	S	12	Center	South	● 1/16		<p>DESCRIBE CORNER MONUMENT FOUND</p> <p>Found 5/8" Rebar with 1-1/2" red plastic cap, projecting 4 inches above grd</p> <p>Cap marked: "Northstar PLS 1823"</p> <hr/> <p>DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>DIA</th> <th>TYPE</th> <th>BEARS</th> <th>DIST</th> <th>FACE/MARKINGS</th> </tr> </thead> <tbody> <tr> <td>22"</td> <td>Hemlock</td> <td>N 57° W</td> <td>24.5 FT</td> <td>Part. Healed Double Blaze</td> </tr> <tr> <td>14"</td> <td>Fir stump</td> <td>N 44° E</td> <td>30.8 FT</td> <td>6FT high stump, Healed Double Blaze</td> </tr> </tbody> </table>	DIA	TYPE	BEARS	DIST	FACE/MARKINGS	22"	Hemlock	N 57° W	24.5 FT	Part. Healed Double Blaze	14"	Fir stump	N 44° E	30.8 FT	6FT high stump, Healed Double Blaze
S	12																					
Center	South																					
● 1/16																						
DIA	TYPE	BEARS	DIST	FACE/MARKINGS																		
22"	Hemlock	N 57° W	24.5 FT	Part. Healed Double Blaze																		
14"	Fir stump	N 44° E	30.8 FT	6FT high stump, Healed Double Blaze																		
<p>PHOTO IDENTIFICATION DATA</p> <p>Photo No. <u>None</u></p> <p>Filed At. <u>None</u></p> <p>Obj. Ident. <u>None</u></p> <p>Ident. By <u>None</u></p> <p style="text-align: center;">Signature _____</p>	<p>DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER</p> <p>Take 101 to slab creek road to Forest road 12, follow to line crossing and 4x4. post about 1 mile east of 127 spur, follow posted/blazed line South along timber line to corner approx 500 ft.</p>																					
<p>PLANE COORDINATE POSITION DATA</p> <p>State <u>OR</u> Zone <u>UTM-10M</u></p> <p>North <u>4990334</u></p> <p>East <u>432749</u></p> <p>Estab. By <u>GCDB</u></p>																						

<p>Signature </p>	<p>Title <u>LSIT</u></p>	<p>Division <u>LANDS</u></p>	<p>Hedquarters <u>SPRINGFIELD</u></p>	<p>Date <u>12/2010</u></p>	<p><u>7100-52 (3/68)</u></p>
-------------------	--------------------------	------------------------------	---------------------------------------	----------------------------	------------------------------

CORNER RECORD (PERPETUATION)

<p>MONUMENT : DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT</p>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> REGISTERED PROFESSIONAL LAND SURVEYOR </div> <p style="font-size: 1.2em; margin: 0;"><i>John Ransom</i></p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> OREGON JULY 21, 1992 JOHN C. RANSOM 2561 </div>
--	--

ACCESSORIES : DESCRIBE NEW BT's WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

Painted 6" Band around BT's and painted face blazes, new nails on signs, cleared brush around corner

16" Fir BRS S 41°30' W 17.5 FT Scribed "CS 1/16 S12" BT" on double blaze

New Bearing Tree includes 3/4" Brass washer mkd "LS2561" nailed to face between B & T on lower blaze

New Bearing Tree and Existing trees measured with Staff Compass(15.75°DEC) and tape.

DONE BY: Jonathan Drew TITLE LSIT DATE 12/2010 PLS NO./AGENCY/STATE USDA Forest Service

Certified Cor. Record Prepared? _____ Filed At: _____ DATE _____

REMARKS

Drove Aluminum post 1.5 FT South

Index File No H-23 T. 6S R. 10W M. W.M. Proj No. Panther #2 Cor. CS 1/16

