



OREGON PUBLIC LAND CORNER REPORT / RESTORATION REPORT
Tillamook County Surveyor's Office

SECTION: 1, 6, 31 AND 36	TOWNSHIP: 1 AND 2 SOUTH	RANGE: 9 AND 10 WEST
--------------------------	-------------------------	----------------------

COUNTY: Tillamook	DATE: 6/21/18
-------------------	---------------

CORNER DESIGNATION: SECTION CORNER COMMON TO SECTIONS S36, T.1S R.10W, W.M., S1, T.2S R.10W, W.M., S31, T.1S R. 9W, W.M., AND S6, T.2S R.9W, W.M.	(Please check one)	
	<input checked="" type="checkbox"/>	Condition Report Only
	<input type="checkbox"/>	Restoration
	<input type="checkbox"/>	Rewitness
	<input type="checkbox"/>	Unrecorded
	<input type="checkbox"/>	Reset at surface
<input type="checkbox"/>	Referenced Out	

Previous Rewitnesses, Restorations and Surveys, etc.. A-76, A-194, A-1633, A-1939, A-1986 (1970), A-2786 (1975), A-7573 (2000), B-225, F-17-15, REWITNESS BK 10 PG 80 (1891), F-28-27 (1975), SURVEY NOTES BK 43 PG 58 (1928), REWITNESS BK 7 PG 78 (1991), REWITNESS BK 4 PG 36 (1929) TILLAMOOK COUNTY SURVEY RECORDS.

Found Monument(s) and Accessories (Condition & Source): FOUND 3" TILLAMOOK COUNTY BRASS CAP IN METAL MONUMENT BOX IN GOOD CONDITION; THE MONUMENT IS STAMPED AS SHOWN HEREON. IN 1891, A SPRUCE LIMB WAS SET TO MONUMENT THE SECTION CORNER AND ACCESSORIES WERE SET. IN 1929, W.E. ANDERSON USING U.G. JACKSON'S FIELD NOTES SET A 2" IRON PIPE BUT NO NEW ACCESSORIES. IN 1975, A ROAD REALIGNMENT SURVEY WAS DONE TO MONUMENT THE RIGHT OF WAY OF TILLAMOOK RIVER ROAD. A 5/8" IRON ROD WITH ALUMINUM CAP WITH A TREATED POST AND METAL LOCATION TAG WERE SET AS RIGHT OF WAY MARKERS AND USED AS ACCESSORIES TO THE MONUMENT. IN 1991, AL DUNCAN, TILLAMOOK COUNTY SURVEYOR, SET A 5/8" IRON ROD WITH 3" TILLAMOOK COUNTY SURVEYOR'S BRASS CAP STAMPED "T1S R10W 9W S36 S31 S1 S6 T2S 1991" AND SET 3 NEW ACCESSORIES.

(REWITNESS BK 7 PG 78)) 1.5" IP WEST 30.6, FOUND NOW 18" DEEP AND APPEARS TO HAVE BEEN BROKEN OFF.
 (REWITNESS BK 7 PG 78) 5/8" IR WITH ALUMINUM CAP 35.6 WESTERLY 1' SOUTH OF 4" X4" TREATED POST, FOUND BUT IRON ROD HAS NO CAP.
 (REWITNESS BK 7 PG 78) 72" HAT SECTION POST WITH YMLT 15.2' EAST, FOUND NOW 14.5'
 (REWITNESS BK 7 PG 78) PPOLE #061800 S 9° E 91.87' TO TACK IN SCRIBED TRIANGLE IN SIDE CENTER, FOUND.
 (REWITNESS BK 7 PG 78) 8" DIAMETER TREATED FENCE POST N 30° W 70.21' TO NAIL W/BRASS WASHER IN SIDE CENTER OF POST, FOUND.

YMLT= YELLOW METAL LOCATION TAG

NEW ACCESSORIES:
 MONUMENT WAS TIED DIRECTLY BY GPS.
 WGS 84: N 45° 26' 03" LATITUDE
 W 123° 50' 40" LONGITUDE



Location & Comments: LOCATED ± 8' EAST OF THE CENTER LINE STRIPE ON TILLAMOOK RIVER ROAD; ±.3 OF A MILE NORTH OF THE INTERSECTION OF FRASER ROAD AND TILLAMOOK RIVER ROAD IN A METAL MONUMENT BOX.

Firm / Agency Tillamook County Surveyors Office
Address: 1510 3rd Street Suite C Tillamook, OR. 97141.

Party Chief: Joe Jensen, P.L.S. 60067, Survey Supervisor

Notes: Digital images taken of monument and accessories.

Witnesses: Michael Rice, P.L.S. 86926, Tillamook County Surveyor
 Travis Porter, Survey Tech.

SURVEYOR'S SEAL

**REGISTERED
 PROFESSIONAL
 LAND SURVEYOR**

Joseph V. Jensen

**OREGON
 JANUARY 10, 2008
 JOSEPH V. JENSEN
 60067**

RENEWAL DATE: 08-30-19