



CORNER INVESTIGATION REPORT

FS INDEX ID: V-21

CORNER: SECTION GCDB ID: 600200 DATE: 6/11/2018
TOWNSHIP: 3S STATE: OREGON
RANGE: 8W COUNTY: TILLAMOOK
SECTION: 25, 26, 35 & 36 FOREST: SIUSLAW
MERIDIAN: WILLAMETTE DISTRICT: HEBO
NFSL PROPERTY BOUNDARY CORNER?: YES NO
LINE(S) POSTED: EAST - 1985 NORTH - 2017
MAINTAINED: EAST - NONE
GUARD POST(S): EAST - 1.8 FT

HISTORY OF VISITATIONS:
(1)1884 - H. MELDRUM, GLO SURVEY
(2)1957 - M. WHITMORE, RW2/372
(3)1962 - L.M. ROSEBERRY, BLM RESURVEY, RW1/497 & 499
(4)1965 & 1967 - B. UDELL, CSF# A-1237 & A-1405
(5)1969 - H. RUSSELL, CSF# B-598
(6)1985 - L. BISHOP, CSF# B-1191, B-1195 & B-1196
(7)2013 - T. JONES, CSF# B-3588

CORNER HISTORY:

- (1) ESTABLISHED CORNER, SET POST & 4 BT'S.
- (2) FOUND 3 BT'S, SET FIR LIMB POST & 4 NEW BT'S.
- (3) FOUND FIR LIMB W/ SCRIBE & 7 BT'S, SET IRON PIPE/BRASS CAP.
- (4) FOUND "BRASS CAP(G.L.O.)" & NOTES 4 BT'S SET IN 1957.
- (5) FOUND US CADASTRAL PIPE & BRONZE CAP.
- (6) FOUND IRON PIPE/BRASS CAP & 5 BT'S, SETS ALUMINUM PIPE/ALUMINUM CAP REFERENCE MONUMENT & 3 NEW BT'S.
- (7) FOUND BRASS CAP, REFERENCE MONUMENT & 6 BT'S.

MONUMENT FOUND/SET:

FOUND A 2-1/2" GALVANIZED IRON PIPE WITH A 3" BRASS CAP, PROJECTING 3" ABOVE THE GROUND.

RECORD CORNER ACCESSORIES:

NO TRACE FOUND OF A (1)4" WILLOW
NO TRACE FOUND OF A (1)4" ALDER, (2)12", (3)17" STUB
NO TRACE FOUND OF A (1)4" ALDER, (2)12", (3)17" STUB, (6)STUB
NO TRACE FOUND OF A (1)42" FIR, (3)52" ROT SNAG
AN INDT. SIZE ROTTED FIR STUMP BEARS, N75°E - 75.5 FT, WITH NO MARKS VIS.
AN INDT. SIZE FIR STUMP BEARS, S74°E - 24.9 FT, WITH SCRIBES VISIBLE ON A PREVIOUSLY OPENED SINGLE BLAZE.
AN INDT. SIZE FIR STUMP BEARS, S79°W - 22.4 FT WITH A HEALED SINGLE BLAZE.
A 32" SAWN FIR STUMP BEARS, N48°22'W - 14.8 FT, WITH NO MARKS VISIBLE & A TIN TOP ATTACHED.
A 17" HEMLOCK BEARS, S76°05'W - 28.9 FT, WITH A HEALED DOUBLE BLAZE.
NO TRACE FOUND OF A (6)6" ALDER
A 16" ALDER BEARS, N85°54'E - 15.5 FT, WITH BARK SCRIBE VISIBLE.
AN ALUMINUM PIPE/CAP BEARS, S70°15'21"E - 57.05 FT, MARKED AS DESC. IN (6).

NEW CORNER ACCESSORIES:

A 18" HEMLOCK BEARS, N65°32'W - 35.6 FT, MARKED "X" "BT" ON A DOUBLE BLAZE.
NEW BT INCLUDES A 3/4" BRASS WASHER NAILED BETWEEN "B" & "T" SCRIBES.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: N1°03'56"W - 1263.38 FT & (6)S88°23'55"E - 2548.45 FT

GEODETIC COORDINATES:

LATITUDE: N 45° 16' 26.016"
LONGITUDE: W 123° 37' 34.824"
ELLIPSOID HEIGHT:
DATUM: WGS 84

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST
3106 PIERCE PARKWAY, STE D
SPRINGFIELD, OREGON 97477

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 11/21/2017

REPORT BY: JONATHAN B. DREW II, PLS# 89396, CFedS# 1664

FIELD CREW: ANDREW HILLMAN, SURVEY TECH.
JACOB HUNT, SURVEY TECH.

REGISTERED PROFESSIONAL LAND SURVEYOR

Jonathan B. Drew II

OREGON
DECEMBER 3, 2014
JONATHAN B. DREW II
89396

EXPIRES: 12/31/2019

RECORD MEASUREMENTS:

- (1)S13°30'W - 4.62 FT
- (1,2,3)N83°30'E - 77.88 FT
- (1,2,3)N61°W - 54.12 FT, (6)54.1 FT
- (1,2,3)S77°45'E - 62.7 FT
- (2,4)N76°E - 76.0 FT, (3,6)75.9 FT
- (2,4)S72°30'E - 24.5 FT, (3)24.75 FT, (6)22.1 FT
- (2,4)S80°W - 23.0 FT, (3)22.77 FT, (6)22.8 FT
- (2)N48°W - 15.5 FT, (3)15.18 FT, (4)15.0 FT, (6)15.2 FT
- (6)S75°40'W - 29.0 FT
- (6)N8°W - 4.5 FT
- (6)N86°30'E - 15.5 FT
- (6)S70°16'30"E - 56.9 FT

METHOD OF MEASUREMENT:

TRAVERSE RUN FROM THIS CORNER TO THE SOUTH 1/16 CORNER, SEC. 25 & 26. HELD RECORD BEARING (6)N01°03'56"W FOR BASIS OF BEARINGS.
RETRACED DISTANCE 1263.38 FT
RECORD DISTANCE: (6)1263.60 FT
BT DISTANCES TO ALUMINUM NAIL SET AT SIDE-CENTER, BEARINGS TO CENTER.

CAP DIAGRAM:



THIS DOCUMENT FILED IN CS OFFICE: YES

OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY FILED SEPARATELY