



CORNER INVESTIGATION REPORT

FS INDEX ID: Y-23

CORNER: CENTER-SOUTH 1/16 **GCDB ID:** 640120 **DATE:** 6/11/2018
TOWNSHIP: 3S **STATE:** OREGON
RANGE: 9W **COUNTY:** TILLAMOOK
SECTION: 36 **FOREST:** SIUSLAW
MERIDIAN: WILLAMETTE **DISTRICT:** HEBO
NFSL PROPERTY BOUNDARY CORNER?: YES NO
LINE(S) POSTED: NORTH - 1984 EAST - 1984
MAINTAINED: NORTH - 2018 EAST - NONE
GUARD POST(S): NORTH - 3.5 FT EAST - 4.5 FT

HISTORY OF VISITATIONS:

- (1)1971 - R. MORRIS, CSF# A-2253
- (2)1977 - L. WHITMORE, USFS RECORD
- (3)1984 - J. PROCHNAU, CSF# B-1176

CORNER HISTORY:

- (1) ESTABLISHED CORNER, SET IRON PIPE/BRONZE CAP, SETS CEDAR POST & MARKS 2 NEW BT'S.
- (2) FOUND THE MONUMENT, NOTES BT'S NOW STUMPS.
- (3) FOUND IRON PIPE/BRASS CAP & 2 BT'S, SET 2 ALUMINUM PIPE/CAP MONUMENTS FOR RM'S.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Jonathan B. Drew II

OREGON
DECEMBER 3, 2014
JONATHAN B. DREW II
89396

MONUMENT FOUND/SET:

FOUND A 1-1/2" GALVANIZED IRON PIPE WITH A 3" BRASS CAP, DOWN 8" BELOW GROUND LEVEL.

EXPIRES: 12/31/2019

RECORD CORNER ACCESSORIES:

- A 31" FIR STUMP WITH SCRIBES VISIBLE ON A ROTTED SINGLE BLAZE.
- A 26" ROTTED FIR STUMP WITH NO MARKS VISIBLE.
- A ROTTED WHITE PAINTED CEDAR 4"x4" POST LAYS ON GROUND NEARBY.
- A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR REFERENCE MONUMENT, PROJECTING 4" ABOVE THE GROUND & MARKED AS DESCRIBED IN (3).
- A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR REFERENCE MONUMENT, PROJECTING 5" ABOVE THE GROUND & MARKED AS DESCRIBED IN (3).

RECORD MEASUREMENTS:

- (1)N20°30'E - 12.2 FT, (3)TO FACE
- (1)N59°30'W - 52.7 FT, (3)TO FACE
- (1)NE - 1.0 FT
- (3)N59°08'32"W - 47.24 FT
- (3)N00°15'18"E - 44.71 FT

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ESTABLISHED.

METHOD OF MEASUREMENT:

NO NEW MEASUREMENTS TAKEN, FILED AS CONDITION REPORT.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: (3)N1°32'31"E - 2572.65 FT & (3)S89°13'54"E - 1304.21 FT

GEODETIC COORDINATES:

LATITUDE: N 45° 16' 8.486"
 LONGITUDE: W 123° 44' 0.596"
 ELLIPSOID HEIGHT: ~460 FT
 DATUM: WGS 84

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST
 3106 PIERCE PARKWAY, STE D
 SPRINGFIELD, OREGON 97477

SOURCE: CONSUMER GRADE GPS, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 11/30/2017

REPORT BY: JONATHAN B. DREW II, PLS #89396, CFedS #1664

FIELD CREW: JACOB HUNT, USFS SURVEY TECH
 ANDREW HILLMAN, USFS SURVEY TECH

THIS DOCUMENT FILED IN CS OFFICE: YES
OTHER DOCUMENT FILED WITH CS: NONE

CAP DIAGRAM:

