

SECTION CORNER  $2\frac{1}{2}$  T 2N R 9 W., WM.

HISTORICAL: G.L.O. Pg. 33 2N9 1884 SET 12X12X8


BK. Pg. 2 383 BASALT STONE

STONE WAS RESET AFTER BEING FOUND OUT OF POSITION BY O.S.B.F. SEE RE/WITNESS 6-14-57 IN BK. 2 Pg. 383 C.S. RECORDS

CONDITION GOOD	FOUND	12" X 12" X 8" STONE	G.L.O. Pg. 33
FD ROTTEN REMAINS GONE	10" HEMLOCK	N. 57° W. 68 LKS.	G.L.O. Pg. 33
FD BURNT ROOT IN AREA GONE	8" HEMLOCK	N. 49° E. 37 LKS.	" "
FD SCRIBING VISIBLE	9" CEDAR	S. 21° E. 32 LKS.	" "
FD SCRIBING VISIBLE	8" HEMLOCK	S. 44° W. 51 LKS.	" "
FD SCRIBING VISIBLE	56" FIR STUMP	N. 40° W. 312 FT.	BK. 2 Pg. 383
FD SCRIBING VISIBLE	66" FIR STUMP	S. 81° W. 360 FT.	" "
FD SCRIBING VISIBLE	59" CEDAR STUMP	N. 40° E. 102 FT.	" "
FD SCRIBING VISIBLE	60" FIR SNAG	S. 51 1/2° E. 312 FT.	" "

REWITNESS

I SET 1/2" IRON PIPE WITH 3" BRASS CAP IN 10" CONCRETE CYLINDER AT POSITION OF FOUND ORIGINAL STONE 12X12X8 MARKED ON S.S. \* 84" Hat Section NORTH 12 FEET ONE SIDE



NEW ACCESSORY: DISTANCES TO NAIL WITH WASHER IN FACE

* 8" HEMLOCK	N. 56° W. 1080'	S 2 B-T CS
* 8" HEMLOCK	N. 30° E. 1138'	S 1 B-T CS
* 12" HEMLOCK	S. 77° E. 1083'	S 12 B-T CS
* 13" HEMLOCK	S. 14° W. 1303'	T 2N 29 W S 11 B-T CS

COMMENTS: THIS CORNER IS LOCATED ± 75' EAST OF AN OLD LOGGING AND ± 100' WEST OF A RIDGE TOP. ALSO SET A COUNTY CORNER TAG ON A 10" ALDER ON THE EAST EDGE OF THE ROAD NEAR THE TOP OF A CUT APPROXIMATELY 56' WEST OF THE CORNER

IN THE PRESENCE OF: DAN MCNUTT AL DVORAK

DATE: 8-31-88

PHOTO: REC

= County corner tag affixed.

TITLE