

INITIAL POINT
MANZANITA BEACH

TILLAMOOK COUNTY REWITNESS

149

INITIAL COR. SEC. 29 T 3 N R 10 W., WM.


HISTORICAL: MAP C-62 Survey by V.L. Johnson set 4" x 9" x 17" Marked "X" (1912)

MAPS	Neignty MAPS
A-1729	B-167
B-567	F-14-11
A-1361	"See Section Map"
A-1951	
F-4-6 O.S.H. Found & Tied Corner to Road	

CONDITION FOUND: AFTER LOCATING THE APPROXIMATE POSITION, I FOUND A 2" IRON PIPE AT GROUND LEVEL. I PROCEEDED TO DIG - NOT DISTURBING THE FOUND IRON PIPE - TO A DEPTH OF 3 FEET. AT THIS POINT I FOUND THE ORIGINAL STONE WITH LEAD PLUG AND TACK. AT THIS TIME I MARKED THE POSITION OF THE FOUND IRON PIPE - South 0° 55' East 0° 40' - AND REMOVE IT. I PLACED A BRASS CAP (by Tape and Transit) DIRECTLY OVER THE FOUND STONE AND I REPLACED COMMENTS: THE FOUND IRON PIPE IN ITS POSITION (S 0° 55' E 0° 40')

REWITNESS

1 SET 2" IRON PIPE WITH 3" BRASS CAP
1971 - Tile & Cement
Post N.W. feet
Hot Section S. E.



NEW ACCESSORY:

ROCK NAIL	NO 1° E 7 99	
POWER POLE	S 20° W 13 19	
"X" CENTER OF FIRE HYDRANT	N 27° E	44 98
24" PINE FINISH NAIL	EAST 31 15	
"X" IN S.E. CORNER CONCRETE PAD	N 30° W	60 94

COMMENTS:

Building # 595
Fire Hydrant

Corner check 1971 Gale Arthur Page Knuppel

CONC. LANEDA AVE

IN THE PRESENCE OF:

GALE ARTHUR

AL DUNCAN GEORGE URREY

DATE: 1970

PHOTO:

* = County corner tag affixed.

GWA