

TILLAMOOK COUNTY REWITNESS #248

W. 36 SEC. 36 31 T 15 R 10 9 W., WM.

1/4 COR. E. 31

HISTORICAL: 1884 GLO--SET POST-- 16° HEM. N 44° W 31 Links
 32° HEM S 25° E 5 Links
 1889 Bk 10 Page 73--SET POST-- HOLD WITNESS 5 25° E 5 LKS
 50° Spr. STUMP N 43° W 6.3 LKS


1885 Book H Page 47 1920-1919 COATES MAPS A117 & B105
 1900 MAP F40-209 1947 MAP A-299 SHEPPARD MAPS F-15-16
 1948 FORREST Found 1 3/4" Iron Pipe Bk 43 Page 56
 1930 W.E. Anderson MAPS F-15-16 F-2-7 A-149 F17-15
 1954 J.L. Carlich Found Old BT MAP 40-150 J.L. CARLICH 1969 A-1842 & A-1726
 1966 J.L. Carlich MAP A-1345 & A-1374 1929 W.E. ANDERSON BK 43 P 56

CONDITION	FOUND:
	1 1/2" Iron Pipe with tack ± 3 1/2 feet deep.
	30" Stump MARKED 1/4 S -- Scribing was exposed

COMMENTS:

REWITNESS

1 SET 1 1/2" Iron Pipe with 3" Brass Cap inside a 3" Iron Pipe flush with pavement
 "x" "x" "Post W. West 138 feet
 96 " Hat Section



NEW ACCESSORY:

Punch Mark Westside of 36" Culvert	S73°E	25 5'
30" Spruce Stump	S07°W	121 60

COMMENTS: SET CAP OVER FOUND 3" IRON PIPE
 A.E. DUNCAN TRAVERSED FROM SECTION CORNER 25 130 TO 1/4 CORNER 36 31.
 A.E. DUNCAN RETRACED W.E. ANDERSON'S FIELD AND FOUND THE 1/4 CORNER.
 (Bk 43 Page 56) WORK

IN THE PRESENCE OF: ALLEN DUNCAN
 GALE ARTHUR
 GARY M° GUIRE

DATE: 7-16-68

PHOTO#: REC

TILLAMOOK COUNTY REGISTER

TITLE

* = County corner tag affixed.

GWA