

16	15
21	22

TILLAMOOK COUNTY REWITNESS

#303

N.W. 22 SEC. 16/15  
 COR. 21/22 T 15 R 10 W., WM.  
 S. E. 16

HISTORICAL: GLO Pg 33 SET POST ± 1957

BOOK	PAGE	MAPS
10	71	A-446
		A-876
		A-959

CONDITION	FOUND:	3/4" IRON PIPE	CZ?
FD ROTTEN STUMP?	20" HEMLOCK	N 85° W 22 LKS	GLO Pg 33
GONE	40" HEMLOCK	S 36° W 61 LKS	GLO Pg 33
GONE	24" HEMLOCK	S 50° E 76 LKS	GLO Pg 33
FD ROTTEN SNAG?	35" HEMLOCK	N 63° E 84 LKS	GLO Pg 33
FD CZ BTs	49" HEMLOCK STUMP	N 18° E 37 4/8	DISTANCE TO FACE
FD CZ BT	30" HEMLOCK STUMP	S 59° E 32 0/8	1" " TO NAIL
FD CZ BT	36 HEMLOCK STUMP	S 30° E 49 7/8	" " TO NAIL

COMMENTS:

REWITNESS

I SET 2" IRON PIPE WITH 3" BRASS CAP IN 10" TILE & CEMENT OVER FD 3/4" IP  
4" x 4" x 60" Post WEST 1 5/8 feet  
" Hat Section SOUTH 1 5/8 FEET

S16/S15  
 S21/S22  
 RS 287  
 1976

NEW ACCESSORY:


COMMENTS: THIS CORNER IS LOCATED ON THE WEST SIDE  
OF A RIDGE ± 150' FROM THE TOP AND ± 100 FEET SOUTH OF A STEEP  
BANK.

IN THE PRESENCE OF: GALE ARTHUR, DAN MCNUTT,  
KEVIN DUNN

DATE: 2-13-76

PHOTO#: NWO-B 8-67

TITLE

\* = County corner tag affixed.