

TILLAMOOK COUNTY REWITNESS # 327

N.W. 32 SEC. 30/29
 COR. 31/32 T 15 R 10 W., WM.
 S. E. 30

HISTORICAL: G.L.O. Pg. 38 1850± 1857

| BOOK | PAGE | MAP |
|------|------|--------|
| 5 | 205 | A-1781 |
| | | B-786 |
| | | |
| | | |


CONDITION GOOD FOUND: 1 1/4" I. P. WITH PLUG & TACK

| | | | |
|--|-------------|---------------------|---------------|
| NOT FOUND | 37" HEMLOCK | N. 57° E. 65 LKS | G.L.O. Pg. 38 |
| NOT FOUND | 36" HEMLOCK | N. 22° W. 9 LKS | G.L.O. Pg. 38 |
| ED. ROTTEN SNAG | 28" HEMLOCK | S. 76° W. 49 LKS | G.L.O. Pg. 38 |
| NOT FOUND | 38" HEMLOCK | S. 54° E. 11 LKS | G.L.O. Pg. 38 |
| NOT FOUND | 18" HEMLOCK | S. 55° E. 23.90 FT. | BK. 5 Pg. 205 |
| NOW 30" SNAG 15' HIGH 26" SCRAMBLING VISIBLE | 24" HEMLOCK | N. 29° E. 26.84 FT. | BK. 5 Pg. 205 |
| NOW 36" STUMP N43°W 29.6' | 30" HEMLOCK | N. 27° W. 31.50 FT. | BK. 5 Pg. 205 |

COMMENTS: 30" HEMLOCK STUMP N82°E 23.9 TO CENTER UNRECORDED
 FA WITH BOTTOM OF FACE

REWITNESS

I SET 2" IRON PIPE WITH 3" BRASS CAP IN 10" TILE & CONCRETE @ POSITION OF ED. 1 1/4" IRON PIPE
 4"x 4"x 60" Post EAST 22 feet
 " Hat Section S. E.



NEW ACCESSORY:

| | | |
|--|--|--|
| | | |
| | | |
| | | |
| | | |

COMMENTS: THIS CORNER POSITION CONFIRMED BY A TIE BY W. E. ANDERSON TO AVALON. CORNER IS LOCATED ON A RIDGE ± 150' SOUTH OF A LANDING AT THE END OF A SHORT SPUR LOGGING ROAD.

IN THE PRESENCE OF: DAN MCNUTT GALE ARTHUR

DATE: 4-11-78

PHOTO#:

* = County corner tag affixed.

TITLE