

TILLAMOOK COUNTY REWITNESS #408
 N.W. 35 SEC. 34 26
 COR. T 25 R 9 W. WM.
 S.W. 26 I SET 10" TILE & CEMENT AROUND
 2 FOUND REFERENCE MARKS CON-
 SISTING OF 3/4" I. P. WITH 2 1/2" G.L.O. BLS

S. 35 RM IS LOCATED
 ± 10' EAST OF THE ROAD
 CONDITION

U.S. GENERAL LAND OFFICE
 T 25
 R 9 W
 S 35
 1956

U.S. GENERAL LAND OFFICE
 T 25
 R 9 W
 S 26
 1956

MADS Books, Pg.
 B-404 G.L.O. 334
 F-40-193
 A-448

RMS 26 IS LOCATED ±
 50' EAST OF THE ROAD

GOOD	S 35 R.M.	S. 76° E. 26.29'	*HAT SEC. 15 WEST
GOOD	S 26 R.M.	N. 34° E. 49'	*18" HEM 15 EAST
NOT FD.	16" HEMLOCK	N. 66° W. 21 LKS.	G.L.O. Pg. 3
NOT FD.	80" CEDAR	S. 59° W. 33 LKS.	G.L.O. Pg. 4
NOT FD.	32" HEMLOCK	N. 51° E. 69 LKS.	G.L.O. Pg. 4
NOT FD.	32" HEMLOCK	S. 57° E. 51 LKS.	G.L.O. Pg. 4

COMMENTS: BOTH RMS FOUND IN MOUND OF STONE

REWITNESS

I SET 10" TILE & CEMENT AROUND FOUND G.L.O. 2 1/2" IRON PIPE
 WITH 3" BRASS CAP IN MOUND OF STONES
 * 84" Hat Section EAST 15 FEET

U.S. GENERAL LAND OFFICE
 T 25 R 9 W
 S 34 | S 26
 S 35
 1956

NEW ACCESSORY:

COMMENTS: THIS CORNER IS LOCATED @ ±
 THE WEST EDGE OF A DEAD END GRAVEL LOGGING
 ROAD, # M 600.

IN THE PRESENCE OF: DAN MCNUYT GALE ARTHUR

DATE: 4-12-79

PHOTO#: 6/21/79 [Signature] G.S.
 TITLE

* = County corner tag affixed.