

21 22
28 27

TILLAMOOK COUNTY REWITNESS

#410

10¹ SEC. 2122
COR. 2827 T 2 S R 9 W., WM.

HISTORICAL: G. L. O. Pg. 725, 9 1857

Book	PAGE	MAPS
1	87	B-862 B-404
4	72	A-4150 A-4892
4	75	A-893
6	243	A-965


CONDITION GOOD FOUND: 5/8" I. R. WITH 1/2" ALUM CAP BK. 6 Pg. 243

GONE	8" SPRUCE	N. 43° E 11 LKS	GLO. Pg. 7
NO 36" ROTTEN HEM. STUMP AXE MARKS	12" SPRUCE	S. 48° E 9 LKS	GLO Pg. 7
GONE	12" SPRUCE	S. 46° W. 16 LKS	GLO Pg. 7
GONE	8" SPRUCE	N. 45° W. 19 LKS	GLO Pg. 7
NOW 38" ROTTEN STUMP SCRIBING VISIBLE	36" HEMLOCK	N. 62° E 31 1/2 FT.	BK. 4 Pg. 72 & 75
NOW 12" ROTTEN WINDFALL	6" HEMLOCK	N. 76° 30' W 15 1/2 FT.	BK. 4 Pg. 72 & 75
NOW 42" CEDAR SCRIBING VISIBLE	30" CEDAR	S. 2° 30' W 10 1/2 FT.	BK. 4 Pg. 72 & 75

COMMENTS:

REWITNESS

1 SET 1 1/2" IRON PIPE WITH 3" BRASS CAP IN 10" CONCRETE CYLINDER
OVER FD. 5/8" I. R. WITH 1/2" ALUM. CAP. BK. 6 Pg. 243
* 72" Hat Section 15 NORTH



NEW ACCESSORY: WAYNE COOK B.T.S Book. 6 PAGE. 243

10" ALDER	N. 14° E. 62 1/2 FT.	T 2 S R 9 W S 22 B T
18" X 15" HEM. STUMP	S. 14° E. 13 1/2 FT.	T 2 S R 9 W S 27 B T
12" HEMLOCK	N. 39° W. 23 1/2 FT.	T 2 S R 9 W S 21 B T

DISTANCES TO NAIL WITH WASHER IN FACE

COMMENTS: THIS CORNER IS LOCATED ± 70' NORTH
OF A SMALL GULLY AT THE EDGE OF A CLEAR CUT.
ALSO FOUND 1" O. D. IRON PIPE WITH PLUG & TACK LAYING ALONG-
SIDE FD. 5/8" I. R.

IN THE PRESENCE OF: DAN MCNUTT AL DVORAK

DATE: 8-16-86 PHOTO#: 8-18-1986 (1/1/1) S. McManis

* = County corner tag affixed.

TITLE