

TILLAMOOK COUNTY REWITNESS #483
 SEC. 1/4 COR. 35136 T 3S R 8 W., WM.

HISTORICAL: GLO Pg 10 358 1884

BK	Pg.	MAPS
3	60 UDELL	BASED ON B-598 PROPORTION UDELL
2	372 WHITMORE	BASED ON B-607 PROPORTION UDELL
		A-1405 PROPORTION UDELL

CONDITION

FOUND; NOTHING FD @ CORNER POINT


FD. REMAINS OF ROTTEN STUMP @ POSITION	48" FIR	N67°E 114 LKS	GLO
FD. REMAINS OF ROTTEN STUMP @ POSITION	50" FIR	S51°W 97 LKS	GLO
NOW 36" S 69-57E 24 ⁸⁹ TO NAIL IN FACE	30" FIR	S 41°E 28 1/2 FT SLP.	2 / 372
NOW 40" N 10°49'W 38 ⁸¹ TO OLD FACE	32" FIR	N 27°W 30 1/2 FT. SLP.	2 / 372

60" FD. UDELLS CORNER INTACT
 FD. SNAG WITH ORIGINAL LINE BLAZE S 0°36'W 36'

R. MORRIS, O.S. FD. LS401; L. HUNNEMULLER, USFS LS1050, J. HANNA, LINCOLN COUNTY SURVEYOR CONCORD IN THE CORNER EVALUATION.

REWITNESS

1 SET 1 1/2" IRON PIPE WITH 3" BRASS CAP IN 10" CONCRETE CYLINDER
 FROM FOUND REMAINS OF ORIGINAL B.T.S.
 * 60" Hat Section NORTH 15'



NEW ACCESSORY: DISTANCES TO NAIL WITH BRASS NAILER IN FACE

* 14" FIR	S 87°32'W 38 ⁸⁹	S 35 B.T. CS
* 36" FIR OLD WHITMORE BT	S 69°57'E 24 ⁸⁹	S 36 B.T. CS

COMMENTS: THIS CORNER IS LOCATED S 9°45'38"E 178⁸¹
 FROM FOUND PROPORTION 1/4 CORNER SET BY BURT UDELL CS MAP# A-1405.
 BASIS OF MERIDIAN IS USFS NORTH SEEKING GYRO. TOPO CALLS CHECKED
 BY U.S.F.S. NORTH FIT EXCELLENT FOR FIRST TWO ORIGINAL CALLS.

IN THE PRESENCE OF: ALLAN E. DUNCAN LS 793 DAN MCNUIT

DATE: 6-25-84

PHOTO#: 6/30/84

Allan E. Duncan, CS
 TITLE

* = County corner tag affixed.