

USDA FOREST SERVICE

Index File No. _____ CORNER RECORD (SEARCH) (Ref. FSM 7151.4) Tract or Survey No. _____ Cor. No. A-15

T. 3S R. 9W R.D. HeBo County TILLAMOOK # 489

Merid. WILL. N.F. SIUSLAW State ORE.

CORNER DIAGRAM

DESCRIBE CORNER MONUMENT FOUND

WILKES, GLO 1896, SET A POST IN A ROCK MOUND.
 & MARKED:
 16" ALDER, S. 77° W., 16 LKS.
 14" FIR, S. 55° W., 36 LKS.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

FOUND 3X3X48 CEDAR STAKE IN ROCK MOUND.
 FOUND 25" ALDER, S. 77° W., 10 FT. WITH VISIBLE BARK SCRIBE 1/4".

PHOTO IDENTIFICATION DATA

Photo No. _____
 Filed At. _____
 Object Ident. _____
 Ident. By _____
 Signature _____

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

THE ORIGINAL SW FIR BT IS GONE.

PLANE COORDINATE POSITION DATA

State _____ Zone _____
 X _____
 Y _____
 Estab. By _____
 Agency _____

(over)

Signature Leonard Whitmore Title Forestry Tech Division Timber Headquarters Hebo Date 11-28-69 7100-52 (3/68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

I SET ALUMINUM GUARD POST ALONGSIDE CEDAR POST AND ATTACHED A "PENALTY TO DESTROY" SIGN.

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

I MARK 2 NEW BT'S:
 19" FIR, DUE SOUTH, 15 FT. TO NAIL HEAD AT SCRIBED "B" MKD. 1/4 S 3 BT CS.
 14" HEMLOCK, S. 72° W., 12 FT. TO NAIL HEAD AT SCRIBED "B" MKD. 1/4 S 3 BT CS.

Signature Leonard Whitmore, Deputy Tillam. Co. Surveyor Date 11-28-69

Work Done By _____ Title _____ Date _____ State Registration No. or Agency _____

Certified Cor. Record Prepared? Yes _____ No _____ Filed At: _____ Date _____

REMARKS

L. WHITMORE IS A DEPUTY COUNTY SURVEYOR EMPOWERED TO RE-WITNESS POSITIVE EVIDENCE OF ORIGINAL MONUMENTS.

2/21/75 J.L. Carlin Co. Surveyor

Index File No. _____ T. 3S R. 9W M. WILL. Tract or Surv. No. N 1/2 Cor. Sec. 3