


Index File No. G-21 CORNER RECORD (SEARCH) (Ref. FSM 7151.4) Tract or Survey No. #506 Cor. No. 11
 T. 3S R. 9W R.D. HEBC County TILLAMOOK State ORE.
 Merid. WILL. N.F. SILVSLAW



DESCRIBE CORNER MONUMENT FOUND FOUND 10" FIR FOR COR. 9 MKD;
12" FIR, S. 10° W., 5 LKS.
12" FIR, N. 80° E., 18 LKS.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
FOUND 13" ROTTED FIR STUMP 4 FT. HIGH FOR COR. POINT WITH SCRIBE MKS. 1/4" VISIBLE ON WEST SIDE.
FOUND 26" FIR, N. 80° E., 12 FT. WITH HEALED WITNESS FACE.
FOUND 30" FIR, S. 10° W., 3 1/2 FT. WITH HEALED WITNESS FACE. ORIGINAL BT'S

IDENTIFICATION DATA
 P. ETJ-7-136
 F. HEBC
 Client _____
 by L. Whitmore
 Signature

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

COORDINATE POSITION DATA
 S. _____ Zone _____
 X _____

Signature	Title	Position	Headquarters	Date	7100-52
<u>Leonard Whitmore</u>	<u>Surveyor</u>	<u>Tillamook</u>	<u>Hebc</u>	<u>7-13-71</u>	

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

I SET PIPE IN CENTER OF ROTTED STUMP, SET ALUM. POST ALONG SIDE WITH PENALTY TO DESTROY SIGN ATTACHED.
PUT TIN ON BACKSIDE OF BT MARKED BEARING TREE CUT ABOVE THIS TIN. PAINT RED BAND AROUND BT'S

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

Leonard Whitmore, Tillamook Co. Dep. Surveyor
(Deputized to permit witness positive original measurements)

Work Done By _____ Title _____ Date _____ State Registration No. or Agency _____

Certified Cor. Record Prepared? Yes No Filed At _____ Date _____

REMARKS
None

File No. T. 3S R. 9W M. Tract or Surv. No. 1/4 Cor. 11/12