

39	R. 97	R.D. Hebo	County Tillamook	USFS FILE # R-15
		N.F. Siuslaw	State Oregon	#530
DIAGRAM	DESCRIBE CORNER MONUMENT FOUND 1" pipe set by Carlick which lays 40' South of a brook in Alder Flat. This corner was set by Sam Caddle in 1880. He set a post from which a 8" Alder brs. South 54 lks.			
BRASSCAPPED	DESCRIBE BEARING TREES OR OTHER OFFICIAL MARKS ON THE GROUND 40" fir brs. North 28 lks. In 1956 Carlock scribed 2 B.T. 26" Hem S75W 115.2 feet (slope) 24" Alder N 30W 60. feet			
IDENTIFICATION DATA	Bearing trees fd. Bd. 30" Hem S75W 115.2 (slope) scribing visable Alder is laying on ground			
BTJ6-46	DESCRIBE DEPENDENT FEATURES NEAR BY NEARBY FEATURES ALSO HOW TO REACH CORNER Ed. Old uprooted decayed stump No Evid. of a face or scribing visable.			
COORDINATE POSITION DATA	This corner was established in 1880 by running East from in the original notes Caddle crossed Brook 10 lks. wide at 31.00 chs then set the 1 at 40.00 ch. and continued east crossing the			

Brook at 44.00 chns. This would place the corner to the North of this Brook which a 1" pipe was fd. The ground had been disturbed by an old sawmill. I feel that there wasn't sufficient amount of evid. to brasscap this course. I would recommend that this corner be set by single prop.

W. Richard Rust
 Devil M. Deen
 7/21/70

ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

BRASSCAPPED

FOUND 34" HEMLOCK, S. 77° W., 114 FT. BY CARLICK.
 CARLICK'S ALDER IS FALLEN UPON THE GROUND.
 SCRIBE NEW BT: 2 2" ALDER, N. 47° W., 43 1/4 FT.

BY W. PERRY

Date By W. PERRY Date 1972 State Registration No. of Agency

FILED AT TILLAMOOK COURTHOUSE

REGISTERED LAND SURVEYOR

WILLIAM R. RUST
 JULY 17, 1970
 936