

**CORNER RECORD (SEARCH)**

Tract or Survey No. \_\_\_\_\_  
 File No. Z-21 Hebo County Tillamook  
 T. 33 R. 9W D. Hebo State Oregon # 564  
 Merid. Utlaretta S. Siuslaw

**CORNER DIAGRAM**  
 T3S R9W  
 35 | 36

**DESCRIBE CORNER MONUMENT FOUND**  
 Found stone with X carved on top, 4 notches on west face and 3 notches on north face.  
 Found 4x4 cedar with scribing by Whitmore.

**DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND**  
 12" spruce brs. N82E 54.8 ft.  
 scribed T3S R9W S36 BT (Whitmore's)  
 34" spruce brs. N47W 25.2 ft.  
 scribed T3S R9W S35 BT

**PHOTO IDENTIFICATION DATA**  
 Photo No. \_\_\_\_\_  
 Filed At. \_\_\_\_\_  
 Object Ident. \_\_\_\_\_  
 Ident. By \_\_\_\_\_  
 Signature \_\_\_\_\_

**DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER**  
 Found what could have been orig. alder BT S10E 10.0 ft. as did Whitmore, but this is questionable.

**DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER**  
 From old field in the E 1/2 E 1/2 Sec 2, T4S R9W, go North for approx. 2000' staying east of Creek 200' corner on side hill above old logging on edge of alder type

**PLANE COORDINATE POSITION**  
 Estab. By \_\_\_\_\_ Agency \_\_\_\_\_ Title \_\_\_\_\_ Division ORLS Headquarters 650 Date 1/70

**CORNER RECORD (PERPETUATION)**

**MONUMENT** DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT  
 In position of corner I set a 2 1/2" x 30' iron post with brass cap mkd  
 T3S R9W  
 35 | 36  
 1969 ORLS 650

**ACCESSORIES** DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE  
 Placed original stone and cedar post alongside brass cap.  
 Set 6' steel post with boundary signs facing west.

Work Done By T.O. McCullough Title Surveyor Date 10/22/69 State Registration No. ORLS 650  
 Agency \_\_\_\_\_

Classified Cor. Record Prepared? Yes No Filed At: \_\_\_\_\_ Date \_\_\_\_\_

REMARKS

Witness to the above corner: NONE