


CORNER RECORD (SEARCH) (Ref. FSM 7151.4)		Tract or Survey No.	Cor. No.
No. <u>C-1</u>	R. <u>10 W.D. Hebo</u>	County <u>TILLA</u>	<u>#570</u>
Loc. <u>W.M.</u>	N.F. <u>SIUSLAW</u>	State <u>ORE.</u>	
NEAR DIAGRAM 	DESCRIBE CORNER MONUMENT FOUND		
	<u>GLC 1933. SET BRASSCAP &amp; MARKED:</u> <u>30" HEM., S. 25° E., 12 LKS.</u> <u>25" HEM., S. 60° W., 21 LKS.</u>		
TO IDENTIFICATION DATA		DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND	
to No. <u>ETS-5-128</u>		<u>FOUND 1933 GLC BRASSCAP IN HEAVY SALMONBERRY</u> <u>FOUND ROTTED 25" HEM. STUMP, S. 60° W., 21 LKS. SCRIBE</u> <u>MARKS ROTTED AWAY.</u> <u>THE S.E. BT IS GONE.</u>	
Loc. Ident.		DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER	
Set. By _____ Signature _____		<u>CORNER IS ON RIDGE BEARS E-W.</u> <u>70 FT. SOUTH IS OLD SAND LAKE TRAIL BEARS E-W.</u>	
NE COORDINATE POSITION OF		Signature _____ Date _____	
to _____ Zone _____		<u>Leonard Whitmore 2-12-76</u>	
Set. By _____ Agency _____			

CORNER RECORD (RE-EVALUATION)	
MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT	
<u>SET IRON FENCE POST 1 FT. SOUTH OF BRASSCAP, ATTACH ATTENTION</u> <u>AND "BOUNDARY" SIGNS.</u>	
ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE	
<u>New BT's:</u> <u>2" HEM., S. 36° W., 24 1/2 FT. SCRIBED 1/4 S 1 BT.</u> <u>6" HEM., S. 78° E., 6 FT. SCRIBED 1/4 S 6 BT.</u>	
<u>Leonard Whitmore, Tillamook County Deputy Surveyor 2-12-76</u>	
Work Done By _____	Title _____ Date _____
Side Registration No. _____ or Agency _____	
Certified Cor Record Prepared? Yes No	Filed At _____ Date _____
REMARKS	