

CORNER RECORD (SEARCH) (Rev. FSM #151.4)		Tract Survd. <i>Leonard Whitmore</i>	Signature <i>Leonard Whitmore</i>
No. <i>F-4</i> Survey <i>R. 10 W</i>	R.D. <i>HEBO</i>	County <i>TILLAMOOK</i>	Date <i>3-5-76</i>
No. <i>W.M.</i>	N.F. <i>SUSLA</i>	State <i>ORE.</i>	574
NEAR DIAGRAM 	DESCRIBE CORNER MONUMENT FOUND: TILLAMOOK COUNTY SURVEYOR 1953 SET SPRUCE LIMB HISTORICAL 26" HEM, N. 45° E, 8 1/2 FT. 8" HEM, SOUTH, 54 FT.		
IDENTIFICATION DATA No. <i>ETJ-5-127</i>	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND: POST GONE. FOUND 26" HEM, N. 45° E, 8 1/2 FT. UPROOTED. FOUND A SCRIBED B" ON ROTTED ROOT. FOUND 14" HEM, SOUTH, 54 FT. WITH A BLAZE HEAD HIGH. A RUSTED F.S. BOUNDARY TIN IS ON WEST SIDE.		
Ident. <i>DIRECT</i>	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER: THE COUNTY SURVEYOR APPARENTLY FELT THE SOUTH BT. WAS TOO SMALL TO SCRIBER. AS THE N.E. BT. IS OUT OF POSITION, I USE THE SOUTH BT. DISTANCE AND BEARING TO DETERMINE THE CORNER POINT OVER.		
COORDINATE POSITION DATA Zone:	DISTANCE		
By:	AGENCY		

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

SET 5/8 IRON ROD
 SET IRON FENCE POST 1 FT. NORTH.

ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

I MARK 2 BT'S:
 14" HEM, SOUTH, 54 FT. SCRIBED "NE 1/6 S 7 CS BT."
 19" HEM, N. 10° W, 25 FT. SCRIBED "NE 1/6 S 7 CS BT."
 DISTANCES TO SIDE-CENTER. VAR. 21°
 IRON GATE POST N. 89° W, 7 FT.

Work Done By _____ Title _____ Date _____ State Registration No. _____
 or Agency _____
 Certified Cor. Record Prepared? Yes No Filed At _____ Date _____

REMARKS
Leonard Whitmore, Tillamook County Deputy Surveyor. 3-5-76
 T. 3.5 R. 10 W NE 1/6 Cor. sec. 7