


Index File No. **E-13** CORNER RECORD (SEARCH) Tract or Survey No. **E-13**
 T. **35** R. **10** W.D. **HERO** County **TILLAMOOK** # **584**
 Merid. **1111** N.F. **STUSLAV** State **ORE.**

CORNER DIAGRAM: 

DESCRIBE CORNER MONUMENT FOUND
 G.L.O. 1882 SET POST AND MKD. 4 WITNESSES:
 20" HEM., S. 82° W., 45 LKS.
 9" HEM., N. 65° W., 13 LKS.
 10" HEM., N. 67° E., 23 LKS.
 15" HEM., S. 82° E., 18 LKS.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
 FOUND BLM BRASSCAP
 FOUND 16" HEM., N. 72° W., 13 LKS. (ORIG.) WITH MARKS "S 4" ON ROTTED FACE.
 FOUND 25" HEM., S. 78° E., 18 LKS. WITH "S" SHOWING. (ORIG.)
 THE ORIG. SW BT IS A ROTTED STUB.
 THE NE BT IS ROTTED AWAY.

PHOTO IDENTIFICATION DATA
 Photo No. _____
 Filed At _____
 Object Ident. _____
 Ident. By _____
 Signature _____

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

PLANE COORDINATE POSITION
 State _____ Zone _____
 X _____
 Y _____
 Estab. By _____ Agency _____
 Signature **Leonard Whitmore**
 Date **6-5-68**

UPDATED 1976
 G.L.O. 1933 SET BRASSCAP AND MARKED:
 10" HEM., S. 31° W., 35 LKS.
 20" HEM., N. 52° E., 34 LKS.
 FOUND BC CORNER _____

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT
 THIS OFFICE HAS ~~NO~~ RECORD OF G.L.O. BRASSCAP THAT IS EXISTING.

BRASSCAP IN POSITION

ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE
 REFERENCE A 26" HEM., STUMP N. 26° E., 8'
 SET IRON FENCE POST AND ATTACH "ATTN" AND "BOUNDARY" Signs

Work Done By _____ Title _____ Date _____ State Registration No. or Agency _____
 Certified Cor. Record Prepared? Yes No Filed At _____ Date _____

REMARKS
 FOUND 1882 S.E. BT A 25" HEM. STUMP 5 FT. HIGH WITH VISIBLE S, NW, NE, AND SW BT'S ARE GONE.
 THE 1933 SW BT IS GONE. THE NE BT IS AN UPRIGHT.
 Leonard Whitmore, 2-17-68

