


Index File No. C-13 CORNER RECORD (SEARCH) (Ref. FSM 7151.4) Tract of Survey No. #585 Cdr. No. 160  
 T 3 S R. 10 W R.D. HEBO County TILLA  
 Merid. W. M. N.F. SIVSLAW State ORE.

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND  
 GLO 1933 SET BRASS CAP  
 16" HEM., N. 72° E., 76 LKS.  
 50" SPRUCE, S. 75° W., 56 LKS.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND  
 FOUND 55" SAWED-OFF SPRUCE SW. BT. VISIBLE FOR MARKS "1/4 S."  
 N.E. BT IS GONE.

PHOTO IDENTIFICATION DATA

Photo No. ETS-9-45  
 Filed At. \_\_\_\_\_  
 Object Ident. WITHIN 100 FT.  
 Ident. By. \_\_\_\_\_  
 Signature: \_\_\_\_\_

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER  
 CORNER APPROX. 300 FT. N. OF OLD LOG ROAD.

PLANE COORDINATE POSITION DATA

Signature: Leonard Whitmore Title: Forestry Tech Division: Timber Headquarters: Hebo Date: 2/14/76  
 Estab. By. \_\_\_\_\_ Agency: \_\_\_\_\_

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

SET IRON FENCE POST 1 FT. S.E.



ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

I SCRIBE 2 NEW BT'S:  
 18" HEM., S. 82° E., 11 1/4 FT. SCRIBED "1/4 S3 BT."  
 22" HEM., S. 55° W., 26 5/8 FT. SCRIBED "1/4 S4 BT."  
 DISTANCES ARE TO SIDE-CENTER. VAR. 21°

Leonard Whitmore, Tilla County Deputy Surveyor 2-76

Work Done By: \_\_\_\_\_ Title: \_\_\_\_\_ Date: \_\_\_\_\_ State Registration No. or Agency: \_\_\_\_\_

Certified Cor. Record Prepared? Yes  No  Filed At: \_\_\_\_\_ Date: \_\_\_\_\_

REMARKS:

File No. T. 3 S R. 10 W M. Tract or Surv. No. 1/4 Cor. 4/3