

(Rev. FSM 7151.4)

File No. A-11 Survey No. #587 NO. 1  
3 S R 10 W T.D. HEBO County TILLAMOOK  
 N.F. SUSLEAW State ORE.

Merid. W.M.

**CORNER DIAGRAM**

**DESCRIBE CORNER MONUMENT FOUND**  
 GLO 1933 SET BRASS CAP.  
 2.5" HEM., S. 38° W., 27 LKS.  
 30" HEM., S. 48° E., 63 LKS.

**DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND**  
 FOUND 40" BROKEN OFF HEM., S. 52° E., 41 1/2 FT. VISIBLE  
 SCRIBING 1/4 S 4 BT.  
 FOUND 24" ROTTED OUT HEM., STUMP, S. 44° W., 17 1/2 FT.  
 MARKS ROTTED AWAY.

**PHOTO IDENTIFICATION DATA**  
 Photo No. \_\_\_\_\_  
 Filed At. \_\_\_\_\_  
 Object Ident. \_\_\_\_\_  
 Ident. By \_\_\_\_\_  
 Signature \_\_\_\_\_

**DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER**  
 CORNER IS ON A GENTLE W. SLOPE.  
 1 CHAIN WEST IS A CREEK RUNNING SOUTH.  
 ONCE BEHIND THE CREEK

**PLANE COORDINATE POSITION**  
 State \_\_\_\_\_  
 Estab. By \_\_\_\_\_  
 Agency \_\_\_\_\_  
 Signature \_\_\_\_\_ Title \_\_\_\_\_ Division \_\_\_\_\_ Headquarters \_\_\_\_\_ Date \_\_\_\_\_

Leonard Whitmore Forestry Tech Tillamook Oreg 2-26-76 7100-52 (3/6)

**MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT**  
 SET IRON FENCE POST 1 FT. S.W. OF BRASS CAP. GLO  
1933  
454

**ACCESSORIES: DESCRIBE NEW BT'S, WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE**  
 DESCRIBE SOMER TO POSITION BEYOND  
 SCRIBED NEW BT  
 26" CEDAR, S. 71° W., 70 1/2 FT. SCRIBED 1/4 S 4 BT.  
 14" HEM., S. 46° E., 20 FT. SCRIBED 1/4 S 4 BT.  
 DISTANCES ARE TO SIDECENTER. VAR. 21°

Leonard Whitmore, Tillamook Co. Deputy Surveyor, 2-26-76

Work Done By \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_ State Registration No. \_\_\_\_\_  
 or Agency \_\_\_\_\_

Certified Cor. Record Prepared? Yes No Filed At \_\_\_\_\_ Date \_\_\_\_\_

REMARKS

Index File No. T. 3 S R. 10 W M. Tract or Surv. No. N 11 Cor. Sec