


Index File No. **J-13** CORNER RECORD (SEARCH) (Ref. FSM 7151.4) Tract or Survey No. _____
 Section **35** R. **10W** R.D. **HEBO** County **TILLA** Cor. No. _____
 Merid. **Will.** N.F. **SUSLAW** State **ORE.**

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT ~~FOUND~~ **GLC 1882 SET POST & MARKED**
8" HEM, S. 2° E., 23 LKS.
18" HEM, N. 38° E., 21 LKS.
20" HEM, S. 75° W., 79 LKS.
74" HEM, N. 59° W., 34 LKS.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
M. WHITMORE, USFS, 1954 SET POST AND SCRIBED
4 NEW BEARING TREES.
AT THAT TIME HE FOUND SCRIBING ON THE
ORIG. N.W. AND S.W. BT'S.

PHOTO IDENTIFICATION DATA

Photo No. _____
 Filed At _____
 Subject Ident. _____
 Ident. By _____
 Signature _____

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
FOUND ALL OF WHITMOR'S BT'S WITH HEALED
WITNESS FACES.
THE CORNER IS 24 FT. EAST OF A SPRING BRANCH
RUNNING SOUTH.

PLANE COORDINATE POSITION DATA

State _____ Zone _____
 Stationed By _____
 Agency _____

Signature _____ Title _____ Division _____ Headquarters _____ Date _____
 7100-52 13 65

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT
SET 3/4 GALV. PIPE 20" ABOVE GROUND ALONGSIDE POST SET BY
WHITMORE 1954.

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

WHITMOR'S BT'S MARKED IN 1954;
"FIR, N. 44° W., 10 FT.
"FIR, N. 55° E., 10 1/2 FT.
"FIR, S. 14° E., 24 1/2 FT.
"SPRUCE, S. 34° W., 25 1/2 FT.

Work Done By _____ Title _____ Date _____ State Registration No. or Agency _____
 Certified Cor. Record Prepared? Yes No Filed At _____ Date _____

REMARKS

2-24-1981 Allan G. Duncan C.S.

Index File No. **T. 35 R. 10W M.** Tract or Surv. No. **9/10** Cor. Sec. **13**
10/15