



TILLAMOOK COUNTY REWITNESS #620

~~NEW~~ SEC. 5
 1/16 COR. 18
 19 T 3 S R 10 W., WM.
 S. E. ~~DEC.~~

HISTORICAL: MAP A-1580 by AL E. Duncan

CONDITION	FOUND:

COMMENTS: THIS AN ESTABLISHED CORNER SET BY AL DUNCAN^{RS793} IN JUNE 1968

9 01 1974

THIS IS AN ESTABLISHED CORNER

1 1/2" x 30" Iron Pipe with a 3" Brass Cap. ^{SET IN TILE AROUND IRON PIPE AND FILLED WITH CONCRETE} Marked as sketched

"x" "x" "Post N.W. ??? feet

96" Hat Section ~~S.E.~~ NORTH 1/3

NEW ACCESSORY:			Scribed as follows:
*6" Pine	N 59 3/4° E	10 38	1/16 S18 BT. CS
*16" Fir	S 26 1/2° E	36 50	1/16 S19 BT. CS

1968

COMMENTS: The E 1/16 corner was set 1320⁰⁰ feet from Section Corner on a TRUE WEST LINE. The E 1/16 corner is located in a North-South Gully. The corner is located 35' West of a Ridge which runs N 16° E

IN THE PRESENCE OF: Allen Duncan ^{RS} 793
 Gale Arthur

DATE: 6-11-68 PHOTO: REC

County corner tag affixed. TILLAMOOK COUNTY TITLE