


Tract or Survey No. 2-5 (Ref. FSM 7151.4) County TILLAMOOK State ORE. Cor. No. #643



DESCRIBE CORNER MONUMENT FOUND  
 GLO 1879 MARKED 5 NOTCHES ON E. EDGE OF A 30" X 12" X 10" STONE & MARKED ONE SNAG; 72" DEAD FIR STUB, N. 72° W., 38 3/4 FT.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND  
 FOUND 30 X 12 X 10 STONE LYING ON ITS SIDE IN STONE MOUND. A RUSTED 1 1/2" BROKEN OFF GALV. PIPE WITH A 6" HIGH WOOD PLUG - SETS AT POINT ORIG. STONE SET FOUND ROTTED STUMP, N. 70° W., 39 FT.

IDENTIFICATION DATA  
 to No. \_\_\_\_\_  
 d At \_\_\_\_\_  
 ect Ident. \_\_\_\_\_  
 ht. By \_\_\_\_\_  
 Signature \_\_\_\_\_

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER  
 STONE HAS 5 NOTCHES ON E. SIDE.  
 CORNER IS LOCATED ON A 25% S.W. SLOPE IN YOUNG GRAVE OF FIR.

COORDINATE POSITION DATA  
 te \_\_\_\_\_ Zone \_\_\_\_\_  
 ob. By \_\_\_\_\_ Agency \_\_\_\_\_

Signature Leonard Whitmore Date 4-8-76

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE  
 I SCRIBE 4 TREES;  
 10" FIR, N. 77° E., 28 1/2 FT. SCRIBED: "T3SR10W S 32 BT." VAR. 21°  
 16" FIR, S. 19° 30' E., 24 FT. SCRIBED: "T4SR10W S 5 BT." DISTANCES ARE 1  
 10" PINE, S. 42° 30' W., 16 3/4 FT. SCRIBED: "T4SR10W S 6 BT." CENTER.  
 10" FIR, N. 41° W., 20 5/8 FT. SCRIBED: "T3SR10W S 3 1/2 BT." ATTACH WITH STIKS ON PAGE 1 & 2

Work Done By \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_ State Registration No. \_\_\_\_\_  
 Certified Cor. Record Prepared? Yes No Filed At \_\_\_\_\_ or Agency \_\_\_\_\_

REMARKS  
Leonard Whitmore, Tillamook County Coroner, 4-8-76

T. 3-4S R. 10W SEC 50C Cor. 31/32 615