


FOREST SERVICE No. <b>E-23</b> 4 S R. 8 W R.D. Hebo Will. N.F. SIUSLAW State ORE.	<b>CORNER RECORD (SEARCH)</b> (Ref. FSM 7151.4)	Tract or Survey No. _____ County <u>TILLAMOOK</u> State <u>ORE.</u>	Cor. No. <b>#685</b>
<b>CORNER DIAGRAM</b> 	<b>DESCRIBE CORNER MONUMENT</b> GLO 1933 FOUND 12X12X12 STONE SET BY TILLAMOOK COUNTY SURVEYOR MARKED "1/4" ON NORTH FACE. GLO SET A BRASSCAP AT THE STONE POINT + MARKED; 18" FIR, N. 11° E., 101 FT. 14" ALDER, S. 73° E., 101 FT.		
<b>WITNESS CORNER TO IDENTIFICATION DATA</b> to No. _____ at _____ Sect Ident. _____ It. By _____ Date _____ IE COC 7-1-75 ION D Signature <i>Leonard Whitmore</i> By _____ Agency _____	<b>DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND</b> FOUND PIPE WITH BRASSCAP HANGING ON A WIRE FENCE. PIPE WAS APPARENTLY DISLODGED BY THE COUNTY ROAD CREW. FOUND 33" FIR, N. 14° E., 101 FT. WITH HEALED WITNESS FACE. FOUND 27" ALDER, S. 47° E., 101 FT. WITH VISIBLE SCRIBE MARKS "1/4 S 12". THE BEARINGS DO NOT CORRESPOND TO THE ORIGINAL. DETERMINE CORNER POINT BY INTERSECTION OF RECORDED DISTANCES. THE TRUE CORNER POINT IS ON NORTH SHOULDER OF NEST-UCCA RIVER ROAD AT THIS POINT I SET 3/8" IRON ROD 3 FEET DEEP WITH THE TOP FLUSH WITH ROAD SURFACE.		

CORNER RECORD (PERPETUATION)			
<b>MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT</b> AS A WITNESS CORNER I SET THE 1933 GLO BRASSCAP 13 FT. DUE NORTH TRUE CORNER POINT AT TOP OF ROAD DRAIN. SET IRON PENCE POST 12 FT. S.E. OF B.C. WITH "PENALTY TO DESTROY" AND PA BOUNDARY SIGNS ATTACHED. <i>Leonard Whitmore</i>			
<b>ACCESSORIES: DESCRIBE NEW B.T.C. WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE</b>			
Work Done By _____	Title _____	Date _____	State Registration No. or Agency _____
Certified Cor. Record Prepared? Yes _____ No _____		Filed At: _____	Date _____
REMARKS			