

Index File No. **B-13**

REVISION 1974
CORNER RECORD (SEARCH) Tract or Survey No. _____
(Ref. FSM 7151.4)

Cor. No. _____

T **4S** R. **8W**

R.D. **Hebo** County **TILLA.**


#662

Merid. **WILL.**

N.F. **SIU-SLAW** State **ORE.**

CORNER DIAGRAM

N 1/16



DESCRIBE CORNER MONUMENT FOUND

PROPORTIONED BY CARTER, BRINGLE ASSOC. PORTLAND

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

PHOTO IDENTIFICATION DATA

Photo No. _____
Filed At. _____
Object Ident. _____
Ident. By _____
Signature _____

DESCRIBE CORNER LOCATION, RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

THIS IS A CERTIFIED CORNER WITH 1/2" PIPE 1" ABOVE GROUND AND NO WITNESSES.
I FEEL IT IS NECESSARY TO FURTHER MONUMENT AND WITNESS THIS CORNER.

PLANE COORDINATE POSITION DATA

State _____ Zone _____
X _____
Y _____
Estab. By _____
Agency _____

VER

Signature

Title

Division

Headquarters

Date

7100-52-13

Leonard Whitmore Forestry Tech Insurer *Hebo* 8-27-74

CORNER RECORD (PERPETUATION)

MONUMENT. DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

SET 1/2" IRON ROD 2 FT. ABOVE GROUND ALONGSIDE ORIGINAL 1/2" GALV. PIPE.
SET IRON POST 2 FT. EAST OF CORNER AND ATTACH "PENALTY TO DESTROY" AND PROPERTY BOUNDARY SIGNS.

ACCESSORIES. DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

SCRIBE 2 NEW WITNESSES:
31" FIR, N. 54° W., 9 1/2 FT. SCRIBED "N 1/16 S 4 BT."
17" FIR, S. 20° W., 15 1/2 FT. SCRIBED "N 1/16 S 4 BT."
DISTANCES ARE TO SIDE-CENTER. VAR. 21°

Leonard Whitmore, Tillamook County Deputy Surveyor 8-27-74

Work Done By **LAMBERT** Title **ORLS** Date **1974** Side Registration No. _____ or Agency _____

Certified Cor. Record Prepared? (Yes) No Filed At: *Tillamook courthouse* Date _____

REMARKS

Index File No. _____ T. **4S** R. **8W** M. _____ Tract or Surv. No. **EAST-N. 1/16** Cor. Sec. **4**