

CORNER RECORD (SEARCH) Tract or Survey No. 675
 (Ref. FSM 7151.4) Cor. No. 675
 384S R. 889W Hebo County Tillamook
 Merid. Willamette N.F. Sinalaw State Oregon

CORNER DIAGRAM

| | |
|-----|-----|
| T3S | |
| R9W | R8W |
| 36 | 31 |
| 1 | 6 |

 T4S
 459 458

DESCRIBE CORNER MONUMENT FOUND Found Caudle's 4 BTs as per records. All scribing was missing for the SW, NE & SE BTs but distance and bearing were good. Found slabs laying at base of NW BTs with "K" blazed on face and faint T3. Found 4 new BTs that L. Whitmore scribed in 1968. Found pitch scribed TWP Cor slab of Whitmore's.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

PHOTO IDENTIFICATION DATA
 Photo No. _____
 Filed At. _____
 Object Ident. _____
 Ident. By _____
 Signet

PLANE COORDINATE POSITION
 State _____ Zone _____
 X _____
 Y _____

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT
 true corner position, set a 2"x30" iron pipe with brass cap mkd R9W T4S 1969
T3S
36 31 R
1 6

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED OR WORK DONE.
 A fir snag brs. S107 14.5' - orig scribing gone
 A fir snag brs. N60W 9.9' (orig) faint scribing
 A fir snag brs. N26E 59.4' - orig scribing missing
 A fir snag brs. S37E 102.3' - orig scribing missing
 A 35" fir brs. N3W 72.3 ft - face healed (Whitmore's)
 A 21" alder brs. east 27.0 ft (Whitmore's)
 A 37" fir brs. S51E 70.0 ft - face healed (Whitmore's)
 A 27" fir brs. S11W 55.0 ft - face healed (Whitmore's)

Work Done By McCULLOUGH & BRYAN Title _____
 Certified Cor Record Prepared? Yes No Filed At: _____
 REM: Deposited pitch sl by brass cap and 6" steel post as per F.S. instructions.

S1