


Index File No. J-23	CORNER RECORD (SEARCH) (Ref. FSM 7151.4)		Tract or Survey No. #695	Cor. No.
T. 4S R. 9W	R.D. Hebo	County TILLA.		
Merid. WILL.	N.F. SIUSLAW	State ORE		
CORNER DIAGRAM 	DESCRIBE CORNER MONUMENT FOUND GLO 1898 SET POST & MKD; 30" SNA9, N.46°30'E., 33 1/2 LKS. 30" SNA9, S.24°E., 36 LKS.			
	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND: FOUND 30" SNA9, N.46 1/2°E., 22' FT. WITH VISIBLE OLD SCRIBE MARKS "1/4 S 12 BT," ALL MARKS ON THE ORIGINAL S.E. SNA9 ARE ROTTED AWAY. THE OLD POST IS GONE.			
PHOTO IDENTIFICATION DATA Photo No. _____ Filed At. _____ Object Ident. _____ Ident. By _____ Signature _____	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER			
PLANE COORDINATE POSITION State _____ Zone _____ X _____				
Signature Leonard Whitman	Title Forestry Tech	Division Timber	Headquarters Hebo	Date 3-17-72 7100-52 (3/68)

CORNER RECORD (PERPETUATION)			
MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT I SET 2" X 2" X 24" FIR LIMB IN OAK MOUND.			
ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE I SCRIBE ONE NEW WITNESS. A 36" HEMLOCK, S.64°E., 42 1/2 FT. SLOPE DISTANCE TO NAIL HEAD AT SCRIBED "B". SCRIBED "1/4 S 13 BT".			
Leonard Whitman, Tilla, Co. Deputy Surveyor EMPOWERED TO BE WITNESS & Monument Positive Evidence 3-17-72			
Work Done By _____	Title _____	Date _____	State Registration No. or Agency _____
Certified Cor. Record Prepared? Yes _____ No _____	Filed At: _____	Date _____	
REMARKS CORNER IS LOCATED AT WEST EDGE OF ALDER PATCH. PAINT RED BAND AND ATTACHED LOCATION TINS ON WITNESS WITNESSES.			
Index File No. T. 4S R. 9W M.	Tract or Surv. No. 112		Cor. 13