

Sect. No. <u>5-9</u> Twp. <u>10W</u> Merid. <u>Willamette</u>	CORNER RECORD (SEARCH) (Ref. FSM 7151.4) Hebo County Tillamook Siuslaw State Oregon	Tract or Survey No. _____ Cor. No. #728
CORNER DIAGRAM SCRIBE CORNER MONUMENT FOUND		
T4S R10W Found 1"x49" iron pipe		
SCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND		
26" snag brs. N59E 83 ft (found rotted slab on ground with scribing T4S barely visible - nailed slab on snag)		
42" fir brs. S33½E 31 ft		
36" cedar snag brs. S57W 8.5 ft - no scribing visible but has axe blaze		
12" spruce brs. N21W 40 ft		
PHOTO IDENTIFICATION DATA		
Photo No. _____	_____	
Filed At. _____	_____	
Object Ident. _____	_____	
Ident. By _____	_____	
Signature _____	_____	
PLANE COORDINATE POSITION		
State _____	Zone _____	_____
ESICD. BY _____	_____	_____
Signature _____	Title _____	_____
_____	Division _____	Headquarters _____
_____	_____	Date _____ 7100

CORNER RECORD (PERPETUATION)		
MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT		
Set 2"x30" iron pipe with brass cap mkd	T4S R10W	
	$\begin{array}{r} 3 \quad 9 \\ 17 \quad 16 \\ \hline 1970 \\ 650 \end{array}$	
ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE		
14" alder brs. N30E 19.2 ft - scribed T4S R10W S9 BT		
14" alder brs. S17W 16.6 ft - scribed T4S R10W S17 BT 650		
Drove steel fence post 5' south of corner with F.S. and attention sign facing west and a fence post 5 feet west of corner with F.S. boundary sign facing south. Placed BT signs and painted red band on all BTs. Drove 1" pipe alongside monument.		
Done By <u>T. C. McCullough</u>	Title <u>Surveyor</u>	Date <u>6/3/70</u> State Registration No. <u>ORLS 650</u>
Filed Cor. Record Prepared? Yes <input type="checkbox"/> No <input type="checkbox"/>	Filed At: _____	Date _____
REMARKS		
witnesses to the above corner: Dick Bryant Dave Moore		