

No. 15 CORNER RECORD (SEARCH) (Ref. FSM 7151.4) Tract or Survey No. Revision
65 R. LOW R.D. HERB County TILLAMOOK State ORE. 1975 975
 D. WILL N.F. SIUSLAW

DESCRIBE CORNER MONUMENT FOUND C.L. 1890 SET POST & MKD.
4" VINE MAPLE, S. 31° W., 13 LKS.
20" SPRUCE, N. 20° W., 18 LKS.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
 By RECORD R. STEWART, LONGVIEW-FIBRE, 1969, FOUND ORIGINAL BT AND 2" X 2" SPRUCE LIMB FOR CORNER. He ADDED 1 1/4" X 3/8" STAINLESS STEEL PIPE ALONGSIDE POST.

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER.
 THE CORNER IS 480 FT. SOUTH OF A RIDGE BEARING EAST AND WEST.

Signature: Leonard Whitmore Date: 12-8-72

Done By: _____ Title: _____ Date: _____ State Registration No. or Agency: _____
 Certified Cor. Record Prepared? Yes No Filed At: _____ Date: _____

REMARKS

T. 6 S. R. 10 W. EAST. S 1/6 Cor. 3

DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT
galvanize pipe
SET IRON FENCE POST 1 FT. E. WITH "PENALTY TO DESTROY" AND BEHIND SIGN
ATTACHED.

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE
 DESCRIBE 2 NEW BT'S:
28" Hemlock, N. 38° E., 55 1/2 FT. SCRIBED "S 1/6 S 2 BT."
28" Hemlock, S. 69° W., 62 1/2 FT. SCRIBED "S 1/6 S 3 BT."
Leonard Whitmore, Forestry Tech. 8-14-75
Lambia Schuster, Forester

Done By: _____ Title: _____ Date: _____ State Registration No. or Agency: _____
 Certified Cor. Record Prepared? Yes No Filed At: _____ Date: _____

REMARKS