

UPDATED 2-1973
CORNER RECORD (SEARCH)

Tract or Survey No. _____ Cor. No. **E-5**

No. **E-5** R.D. **HeBo** County **TILLAMOOK**

6.5 R. 10W N.F. **SILSLAW** State **ORE.** 12-31-68

id. **Will**

NEAR-DIAGRAM

6
7
8

DESCRIBE CORNER MONUMENT FOUND GLO 1890 SET A POST FROM
 A 24" ALDER, N. 56° W., 38 LKS.
 A 24" ALDER, N. 42° E., 70 LKS. **#982 WHICH**
 A 5" HEM., S. 32° W., 11 LKS.
 A 12" HEM., S. 40° E., 4 LKS.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
 M. WHITMORE, USFS, 12-18-56 FOUND IRON PIPE 24" HIGH
 FROM WHICH:
 A 24" HEM., S. 40° E., 4 LKS. WITH HEALED WITNESS FACE
 A 10" DEAD HEM. STUB, S. 32° W., 11 LKS. WITH MKS. SHOWING
 THE ORIG. N.W. AND N.E. BT'S ARE GONE.

TO IDENTIFICATION DATA
 No. **ETJ-5-157**
 At. **7-16-69 PHOTO**
 Ident. **DIRECT**
 By **L. WHITMORE**
 Signature

THE COORDINATE POSITION DATA
 Zone _____

 By _____
 Agency _____

25" SPRUCE, N. 5° W., 113 FT. SLOPE DIST. MKD. T&SR 10W 3
 16" SPRUCE, N. 28° 30' E., 83 FT. SLOPE DIST. MKD. T&SR
 12/31/68 for Tech-Web 5 T&SR 10W 3
 5 BT

COPIED FROM NOTES

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Leonard Whitmore is a Deputy County Surveyor empowered to re-witness
 positive, identifiable found monuments in connection with USFS
 work J.L. Conley
 12/79

ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS, ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

Work Done By _____ Title _____ Date _____ State Registration No. _____
 or Agency _____

Certified Cor Record Prepared? Yes No Filed At: _____ Date _____

REMARKS
 CORNER IS IN GOOD CONDITION.
 of Whitmore 3-73